1	рН	Between	5.5 to 9.0
2	Temperature	Should not exceed 5 c above the ambient temperature of the receiving body	
3	Oil & Grease	Not to exceed	10 mg/l
4	Suspended Solids	Not to exceed	100 mg/l.
5	B.O.D 3 days at 27 0 C	Not to exceed	30 mg/l.
6	C.O.D.	Not to exceed	250 mg/l.
7	Total Dissolved Solids	Not to exceed	2100.0 mg/l.
8	Chlorides	Not to exceed	600 mg/l
9	Sulphates	Not to exceed	1000 mg/l

- (iv) Trade Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall be used on land for gardening. For this sufficient land shall be made available. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids Not to exceed 100 mg/l. (2) BOD 3 days 270 C. Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal	
THE REAL PROPERTY AND ADDRESS OF THE PERSON NAMED IN	Grape Stem	7.0	MT/M.	ann ann	Composting	

(viii)Other Conditions: Industry shall monitor the effluent quantity regularly.

 The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose ... 3.5 CMD
(ii) Water gets Polluted &
Pollutants are Biodegradable ... 50.0 CMD
(iii) Water gets Polluted, Pollutants

are not Biodegradable & Toxic ... 0.00 CMD

(iv) Industrial Cooling, spraying
in mine pits or boiler feed ... 0.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

is Processed through IMIS Application Software. Copyright MPCB.

Page 2 of 5

Sr. No.	Chimney Attached To	Height in Mtrs.
Sr. No.	D.G. Set (80 KVA)	7.0 Mtrs above the
1	* A Samuel Same and the same of the same o	roof of building roof

The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be (iii) open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

HAZARDOUS UNDER 8. CONDITIONS (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall handle hazardous wastes as specified below.

Type Of Waste Quantity Sr. No. The Industry shall not generate any type of Hazardous Waste.

- Treatment: NIL (ii)
- The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- The industry should comply with the Hazardous Waste (M&H) Rules, 2003.

9. Industry shall comply with following additional conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or

ed through IMIS Application Software. Copyright MPCB.

Page 4 of 5