# MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 24020781 / 24010437

Fax : 24024068 / 24044532



Kalpataru Point, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor, Opp. Cineplanet, Near Sion Circle, Sion (E), Mumbai - 400022.

Email : mpcb@vsnl.net

Visit At : <u>http://mpcb.gov.in</u>

### EIC No: MU-3245-12 Infrastructure Project/LSI Consent No. MPCBHQ/ROHQ/Mumbai/COR/CC/369

Date: 02 /05/2012

1

Consent to Operate Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

CONSENT is hereby granted to,

M/s. Bombay Dyeing & Manufacturing Company Ltd, "Spring Mill", C.S. No: 223, 1/128(pt), 120(pt), 1/983, Dadar – Naigaon Division, G.D.Ambedkar Road, Dadar, Mumbai, Maharashtra.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 30/04/2015.

For residential project (Bldg. No: 1) named as M/s. Bombay Dyeing & Manufacturing Company Ltd, "Spring Mill", C.S. No: 223, 1/128(pt), 120(pt), 1983, Dadar – Naigaon Division, G.D.Ambedkar Road, Dadar, Mumbar, Maharashtra on total plot area of 1,85,962.61 Sq.mtrs & Total Built up area of 27,377 Sq.mtrs including utilities for residential project as per construction occupancy certificate issued by local body.

### 2. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of sewage effluent from the factory shall not exceed 159.0 M3.

(ii) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

pH	Not to a	
Sugnanded Galil		6.5 to 9.0
	Not to exceed	100 mg/l.
BOD 3 Days 27 degree C	Not to exceed	
Fecal Coliform		100 mg/l.
Residual Chlorine		500/100/1 mg/l.
		01 mg/l.
6 Detergent	Not to exceed	01 mg/l.
Floating matters	Not to exceed	10 mg/l
	Suspended Solids BOD 3 Days 27 degree C	Suspended SolidsNot to exceedBOD 3 Days 27 degree CNot to exceedFecal ColiformNot to exceedResidual ChlorineNot to exceedDetergentNot to exceed

(iii) Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting and cooling of Air conditioners and remaining shall be discharged to Municipal sewer. In no case, effluent shall find its way to any water body directly/indirectly at any time.

[Project proponent shall operate STP for five years from the obtaining Occupation Certificate]. date of

(1V) No1	wastes:					
Sr.No	Type of Segregated solid waste	Quantity (Kg/Day)	Treatment	Disposal		
1.	Wet Garbage	300	-(0)	Use as		
2.	STP Sludge	50	Composting	Manure		
2.	Dry Garbage	000		landfill		

### 3. **Other Conditions: -**

- All activities shall be in resonance with the provisions of Indian Forest Act, 1927 1. (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments. 2.
- Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority on other relevant authorities, as applicable; 3.
- Near the activities that recelated to water (like activity of water parks, water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5
- In order to ensure that the water from this project do not enter into outside 4. environment, the collas crossing the township/complex premises, shall be lined, covered, and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body. 5.
- Appricant shall draw plans for the segregation of solid wastes into The biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting (i.e vermi-composting facility within premises) with the approval of local body. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and

method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000.

- Applicant shall be responsible to take adequate precautionary measures as 6. detailed in this consent. 7.
- For disinfections of waste water ultra violet radiation shall be used in place of

Z

site

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under The daily water consumption for the following categories is as under: (i) Domestic 220.00 CMD (ii) Water gets Polluted & Pollutants are Biodegradable ... 0.00 CMD (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ... 0.00 CMD (iii) Industrial Cooling, spraying 0.00 CMD The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of 5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT. (i) The Applicant may install 1-no. of diesel generating sets (DG Sets 1000 KVA and shall be equipped with comprehensive control system as is warranted with reference to generations of emissions and operate and maintain the same continuously so as to achieve the level of pollutants to the following a. Standards for Emissions of Air Pollutan (i) SPM/TPM Not to except 150 mg/Nm3 (ii) SO2 (DG Set) Not to exec 33 Kg/dav (ii) The following measures shall be take: a. Adequate mitigation measures shall be taken to control emissions of SO2, NOx, SPM and RSPM. b. Applicant shall achieve following Ambient Air Quality standards. Not to Exceed (Annual Average) 1. SPM 140  $\mu g/m3$ Not to E ceed (24 hours) 200 μg/ m3 2. ot to Exceed (Annual Average) 60  $\mu g/m3$ Exceed (24 hours) 80  $\mu g/m3$ Not to Exceed (Annual Average) 60  $\mu g/m3$ Not to Exceed (24 hours) 80  $\mu g/m3$ RSPM Not to Exceed (Annual Average) 60  $\mu g/m3$ Not to Exceed (24 hours) 100  $\mu g/m3$ (iii) The applicant shall observe the following fuel pattern:-Sr. No. Type Of Fuel Quantity 1 HSD 68 ltrs/Hr The applicant shall erect the chimney(s) of the following (iv) Sr. No. Chimney Attached To Height in Mtrs. 1 D. G. Set 1000 KVA 10.0 Mtrs

### (v) Conditions for D.G. Set

- 1. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- 3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- 5. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer
- 6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- 7. D.G. Set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding area due to operation of DiG. Set.

### (vi) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platformetc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.
- construction material shall be carried in enclosed vehicles during construction activities.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

## Applicant shall not generate any type of Hazardous Waste.

7. The applicant shall adopt environment friendly technology in development of the project.

4

- This Board reserves the right to amend or add any conditions in this consent and the 8. same shall be binding on the Applicant;
- The applicant shall comply with the conditions stipulated in Environment 9. <u>Clearance</u> granted by GOI, vide no: <u>J-12011/57/2005-1A(CIE), dt: 21/03/2006.</u>
- 10. This is issued pursuant to the decision of **Consent Committee** of the Board in its meeting held on 16th March 2012 & approval of chairperson of the Board.
- The applicant shall submit Bank Guarantee of Rs. 10.0 Lakhs towards the 11. compliance of consent conditions at Regional Office, MPCB, Mumbai within 15-days.
- 12. The <u>Capital investment</u> of the total project is <u>Rs. 201.33 Cr</u>.

M/s. Bombay Dyeing & Manufacturing Company Ltd,

G.D.Ambedkar Road, Dadar, Mumbai, Maharashtra.

Copy to-

To,

1. Regional Off MPCB, Mumbai - He is directed to obtain necessary Bank ntee from the applicant and ensure compliance of consent conditions

"Spring Mill", C.S. No: 223, 1/128(pt), 120(pt), 1983, Dadar – Naigaon Division,

- 2. Sub Regional officer-I, Mumbai, MPCB,
- 3. Chie Accounts Officer, Mumbai, MPCB,

Received consent fee of:-

Sr. No.	Amount	DD M		
1		DD. No.	Date	Drawn On
	Rs. 5,06,800/-	015302	03/10/2011	IDBI
2.	Rs. 50,680/-	015303	03/10/2011	
3.	Rs. 5,06,800/-	105352		IDBI
4.	Rs. 50,680/-		28/11/2011	IDBI
		105353	28/11/2011	IDBI

4. Cess Branch, MPCB, Mumbai.

5. Master file.

haiskar)

5

mber Secretary