# MAHARASHATRA POLLUTION CONTROL BOARD

0231-2652952

Email rokolhapur@mpcb.gov.in

Visit At : http://mpcb.gov.in



Udyog Bhawan Near Collector Office,

Kolhapur - 416003

Red/S.S.I

Date: 29 | 05/2012

Consent No: MPCB/RO/KOP/ 1300 /12.

Consent to Opearte under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Trimurti Industries Plot No-F-19,MIDC Islampur, Tal-Walwa Dist. Sangli, Maharastra

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to 31.03.2015.
- 2. The Consent is valid for the manufacture of -

Sr. No. Product Name		
1 Potassium Chloride Powder	Maximum Quantity	UOM
- Inoride Powder	25	MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 1.80M<sup>3</sup>.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 0.40M3.
- (iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Page 1 of 5

This Consent is Processed through IMIS Application Software, Copyright MPCB.

1	рН	D	
2	Temperature	Between	5.5 to 9.0
	All the second s	Should not exceed 5 c	0.0 10 0.0
		above the ambient	
		temperature of the	
3	01100	receiving body	
_	Oil & Grease	Not to exceed	
4	Suspended Solids	Not to exceed	10 mg/l
5	B.O.D.	Not to exceed	100 mg/l.
6	C.O.D.	Not to exceed	30 mg/l.
7	Total Dissolved Solids	Not to exceed	250 mg/l.
8	Chlarid	Not to exceed	250 mg/l.
9	Chlorides	Not to exceed	2100 mg/l
	Sulphates	Not to exceed	600 mg/l
10	R- Chlorine	Not to exceed	1000 mg/l
		Not to exceed	1 mg/l.
Frac	le Efficant Di		g/i.

- (iv) Trade Effluent Disposal: The metal bearing industrial effluent shall be segregated and reused back into process and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises. The industry shall become member of CETP as and when proposed. Industry shall provide necessary facilities to recycle the entire industrial effluent back into the process in six months.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids Not to exceed (2) BOD 3 days 270 C. 100 mg/l. Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

Sr. No. Type Of Wasts				
Sr. No. Type Of Waste	Quantity	UOM	Troot	
	_		Treatment	Disposal
viii) Othor C				

(viii)Other Conditions: Industry should monitor effluent quality regularly.

The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(ii) Water gets Polluted & 0.80 CMD

Pollutants are Biodegradable ... (iii) Water gets Polluted, Pollutants 9.00 CMD

are not Biodegradable & Toxic ... (iv) Industrial Cooling, spraying 0.00 CMD

in mine pits or boiler feed 0.00 CMD

Page 2 of 5

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under

## 5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following

## Standards for emission of Air Pollutants:

- 1. SPM .. Not to exceed 150 ug/Nm<sup>3</sup>
- 2. SO<sub>2</sub> .. Not to exceed 80.0 Kg/D.

#### a. Control Equipment:

Industry shall provide fly ash arrestor of sufficient capacity to the wood fired

### 6. Conditions for D.G. Set .....

## 7. Standards for Stack Emissions:

The applicant shall observe the following fuel pattern:-(i)

Sr. No.	Т		-g ruer pattern;-
1	Type Of Wood	quantity	UOM
	71.000	8000	Kg/D

The applicant shall erect the chimney(s) of the following (ii)

Sr. No.	Chimney Attached To	
1	Baby Boiler	organo in Milis.
() m1	3 - 01101	8.00

- The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate
- The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

#### (vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality

Page 3 of 5

## 8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	28.1 Residue Of Wastes.	50.0	Kg/M	Send to CHWTSDF

- (ii) Treatment: NIL
- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.

#### 9. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection

1AB stropule

system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection

Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

The Capital investment of the industry is Rs. 29.78 Lacs. 10.

(Amar B. Durgule)
I/c. Regional Office, Kolhapur.

To, Trimurti Industries Plot No-F-19, MIDC Islampur, Tal-Walwa, Dist. Sangli.

#### Copy submitted to:

- 1. The Member Secretary, MPC Board, Mumbai.
- 2. The Chief Accounts Officer, M P C Board, Mumbai.
- 3. The Sub Regional officer, MPC Board, Sangli.
- 4 Cess wing/Statistical wing/Air wing/ Hazardous Management Wing,

## Received Consent fee of -

Sr. No. Amount(Pa)			
Sr. No. Amount(Rs.)  1 4800		Date	Drawn On
4800	1578	12. April 2012	
		1	Union Bank Of India.