MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437 24020781/24014701

Fax: 24024068 24023516

Website: http://mpeb.gov.in

E-mail: mpcb a vsnl.net



Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

Red/L.S.I

Consent No:BO/JD(APC)/EICNo.AD-9654-12/E/CC ~ 458

Date 22/6/2012

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Nahar's Engineering (India) Pvt. Ltd., E-95/2, MIDC Waluj,

Aurangabad.

Authorization under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made torther and subject to the following terms and conditions:

- 1. The Consent to Establish is granted for a period up to commissioning of unit or Five years whichever is earlier.
- 2. The Consent is valid for the manufacture of -

SENO	Product Name	Maximum Quantity	UOM
	Wind Shield Powder - sting, CED Coating, Powder coating & Assembly	3000	Nos./Day
2	This Wheeler Body Elemention	1000	Nos./Day

3. CONDITIONS UNDER WATER ACT:

Figure daily quantity of trade effluent from the factory shall not exceed 4.0 M3..

Trade Effluent: Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

N AT	o Parameter		Limits
1	p p	Between	5.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l.
•)	BOD 3 day at 27°C	Not to exceed	30 mg/l
:	000	Not to exceed	250 mg/l
7	Ol & Grease	Not to exceed	10 mg/l
	Total Dissolved Solids	Not to exceed	2100 mg/l
:	Chlorides	Not to exceed	600 mg/l
.	Sulphates	Not to exceed	1000 mg/l

Trade Effluent Disposal: The industrial effluent shall be reused back into process and remaining treated effluent shall be disposed to CETP for further treatment.

Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

	Suspended Solids	Not to exceed	100	mg/l.
_	B(H) 3 days 270 C.	Not to exceed		-mg/l.

Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

AVID Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
	Paper	180,0	Kg/M	<u></u>	Sale
	Metallic scrap	1500.0	Kg/M		Sale

war Other Conditions:-.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

consumption in the prescribed form and pay the Cess as specified under Section 5 of the said Act.

5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of poliutants to the following standards:

a. Control Equipment: Dust collector of sufficient capacity shall be provided to all sources of particulate matter emissions. And scrubber to paint section shall be provided.

Standards for Emissions of Air Pollutants:

SPM/TPM

Not to exceed

150 mg/Nm³

4D SO2

Not to exceed

48 Kg/day

The applicant shall observe the following fuel pattern:-

8.57	o. Type Of Fu	el Quantity	UOM
. 1.	L.P.G	160	Kgs/Hr.

The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
	DG Set 500 KVA	5.0 above roof
* / *** * * * * * * * * * * * * * * * *	Test Bench & Dynamo meter	1.1

- The applicant shall provide ports in the chimney/(s) and facilities such as allow pattern etc. for monitoring the air emissions and the same shall be equilibrium aspection to and for use of the Board's Staff. The chimney(s) vents article literarious sources of emission shall be designated by numbers such as S-1. S-2, etc. and these shall be painted/ displayed to facilitate identification.
- The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 m/A during might time. Day time is reckoned in between 6 a.m. and 10 m/m and might time is reckoned between 10 p.m. and 6 a.m.

Other Conditions:

- 1. The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality is calariy.

Conditions for D.G. Set

- in Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure acoustic treatment of the room should be designed for minimum 15 dB (A) insertion loss or for meeting the ambient noise standards,

- with hever is on higher side. A suitable exhaust muffler with insertion loss at 25-46 Az shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- installation of DG Set must be strictly in compliance with accommendations of DG Set manufacturer.
- A preper routine and preventive maintenance procedure for DG set should most and followed in consultation with the DG manufacturer which would be interprevent noise levels of DG set from deteriorating with use
- 100 Set shall be operated only in case of power failure.
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

in The Industry shall handle hazardous wastes as specified below.

Sr. No. Type Of Waste	Quantity	UOM	Disposal
5.1 Used oil	180	Kg/M	Authorised Reprocessors
2 343 WWT Sludge	100	Kg/M	CHWTSDF
9 USW iste from electro	5	Kg/M	CHWTSDF
· Property of the state of the			

- on Treatment: NH.
- is The authorization is hereby granted to operate a facility for collection, storage, it inspert & disposal of hazardous waste.
- 1. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
 - a. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
 - but shall be ensured that the Hazardous waste is handled, managed & Lapased of structly in accordance with the Hazardous Waste (Management & Finalisms, Rules, 1989 as amended on 2003 and shown & submitted to the Geard as & when asked for

7. Whenever due to any accident or other unforeseen act or even, such emissions was even; apprehended to occur in excess of standards laid down, such entermation shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. Industry shall comply with following additional conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- H. The applicant shall bring minimum 33% of the available open land under green over the tree plantation.
- Scha waste. The non hazardous solid waste arising in the factory premises, sweetches, etc. be disposed of scientifically so as not to cause any nuisance / political. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms a conditions of this consent regarding pollution levels.
- The quality shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Beard.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board to the services rendered in this behalf.
- And The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- whethe term shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment Protection (Second Amendment) Rules, 1992.
- is inspection look shall be opened and made available to the Board's officers iming their visit to the applicant.
- x The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes is sewers down-stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- 9. The total Capital investment of the industry is Rs. 30.51 Crs.
- 10. This is issued with the approval of Consent Committee meeting held on 30/05/2012.
- 11. This consent supersedes the earlier consent granted by Board vide no. SROA-I/Abad/UG/E-25 of 98/CC-315/4711 dated 05/11/2008.

(Milind Mhaiskar, IAS) Member Secretary

To.

M.s. Nahar's Engineering (India) Pvt. Ltd., E-95.2. MIDC Waluj, Aurangabad.

Copy to:

RO-MPCB Aurangabad SRO-MPCB Aurangabad-I CAO Cess Branch/Master File Received Consent fee of -

Sr. N	o. Amount(Rs.)	DD. No.	Date	Drawn On
1	150001-	022843	02/12/2011	Malkapur Urbn Co-op. Bank
. 2	100 -	022842	02/12/2011	Ltd.
ò	60000 -	023542	5/3/2012	