MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 2402 4068

Email: jdwater@mpcb.gov.in

Visit At : http://mpcb.gov.in

http://mnch.gov.in



Kapataru Point 02nd,03rd & 04th floor Opp. Cineplanet,

Near Sion Circle, Sion (E),

Mumbai- 400 022

Red/L.S.I

Date: 09/10/2012

Consent No: Consent No: BO/JD (WPC)/PN-15128-12/E/CC-CAC/MPCB/2012/10/0120

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M, H &TM) Rules respectively].

CONSENT is hereby granted to

M/s. Schreiber Dynamix Dairies Ltd., (Unit -II)

E-250, MIDC Baramati, Tal-Baramati,

Dist-Pune -413133

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Establish is granted for a period up to: Commissioning of unit or 5 years whichever is earlier.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Milk Powders + Baby Food	1500	MT/M
2	Ghee	487	MT/M
3	Butter	478	MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 1350.00M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 150.00M3.

(iii) Trade Effluent:

Treatment: The applicant shall provide separate comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	25	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	10	mg/l.
4	COD	Not to exceed	150	mg/l.
5	Oil & Grease	Not to exceed	10	mg/l.
6	T.D.S.	Not to exceed	2100	mg/l.
7	Chlorides	Not to exceed	600	mg/l.
8	Sulphates	Not to exceed	1000	mg/l.

- (iv) Trade Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall discharge on M/s. Sahyadri Agro Ltd., land as per the agreement.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)Suspended Solids Not to exceed

100 mg/l.

(2)BOD 3 days 270 C. Not to exceed

100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	ETP Biological	92.00	m3/day		used
	sludge				mannure

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

150.00 CMD

(ii) Water gets Polluted &

Pollutants are Biodegradable ...

1350.00 CMD

(iii) Water gets Polluted. Pollutants

are not Biodegradable & Toxic ...

0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed

0.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

- The applicant shall install a comprehensive control system consisting of (i) control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
 - a. Control Equipment: Air pollution control equipments of adequate capacity shall be provided to limit the emissions from all sources of emission.
 - b. Standards for Stack Emissions:

1) SPM

Not to exceed

150 mg/Nm3

2) SO₂

Not to exceed

60 kg/Day

- 6. Standards for Stack Emissions:
- The applicant shall observe the following fuel pattern:-(i)

Sr. No.	Type Of Fuel	Quantity	UOM
1	HSD	3000.00	Lit./Day

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Spray Dryer	37.00
2	D.G set (1500 KVA)	8.00 *

^{(*} above the roof of the building in which it is installed)

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

7. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- d. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f. D.G. Set shall be operated only in case of power failure
- g. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No. Type Of Waste Quantity UOM Disposal
--Industry shall not generate any type of Hazardous Waste --

(ii) Treatment: - NIL

- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
 - b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.

9. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- viii.As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- ix. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 10. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
- 11. Industry shall obtain consent to operate before starting the production activity.
- 12. This Consent is issued pursuant to the decision of Consent Appraisal Committee meeting of Board held on 26/09/2012.
- 13. The Capital investment of the industry (Unit –II) is Rs. 220.00 Crs.

For and on Behalf of the Maharashtra Pollution Control Board,

(Rajeev Kumar Mital) Member Secretary

To, Schreiber Dynamix Dairies Ltd., (Unit -II) E-250, MIDC Baramati, Tal-Baramati, Dist-Pune

Copy to: RO, MPCB, Pune and SRO, MPCB, Pune-I: - They are directed to ensure the compliance of consent conditions.

CAO / Cess Branch / Master File.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	440000	903485	11 Jun 2012	SBI Bank