# MAHARASHATRA POLLUTION CONTROL BOARD

Phone 022-24020781,24014701

Fax : 022-24023516,24093814

Email: jdwater@mpcb.gov.in

Visit At http://mpcb.gov.in



Kalpataru Point, 2nd - 4th Floor Opp, Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022

Red/L.S.I
Consent No.BO/JD (WPC)/ROTN/EIC-TN-3954-12/O/CO/A(-6-7) Date: 4/4 2/2012
Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008
[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Lavino Kapur Cottons Pvt Ltd Plot no H-1, MIDC TARAPUR TAL.TARAPUR DIST.THANE -401506

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&R) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.10.2017.

The Consent is valid for the manufacture of -

Ÿ.	Z. THE COIL	elluis valiu ioi diicane	and the second control of the second control	A Part and the constraint shows a state of the state of t
		Product Name	Maximum	UOM
	Sr. No.		Quantity	
	1	ABSORBENT, COTT	ON 5400	MT/A
		PHARMACOPOCIAL	100mm	
		GRADE		

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 1380.00M3.

(ii) The daily quantity of sewage effluent from the factory shall not exceed  $40.00M_{\odot}^3$ 

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	PΗ	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	100	mg/l.
4	COD	Not to exceed	250	mg/l.
5	Oil & Grease	Not to exceed	10	mg/l.
6	Detergent	Not to exceed	2	mg/l.
7	Phenol	Not to exceed	2	mg/l.

- (iv) Trade Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall be sent to CETP for further treatment & disposal. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
  - Suspended Solids (1)

Not to exceed

100 mg/l.

(2) BOD 3 days 27o C.

Not to exceed

100 mg/l.

- (vi) Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be discharged into sewerage system provided by MIDC.
- (vii) Non-Hazardous Solid Wastes:

A STATE OF THE STA	estatula a ala pubernita politica la la constati li libra albano desc	are contributed and the contributed and the contributed are contributed as the contributed and contributed are	lai si isanka, kutto salah alam alama	MEROMENE SALESTINES AND STORY OF THE SECTION OF	the the state of t
Sr. No.	Type	Quantity	UOM	Treatment	Disposal
	Waste				

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

40.00 CMD

(ii) Water gets Polluted &

Pollutants are Biodegradable

1380.00 CMD

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic.

0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed ... 75.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

### 5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Industry shall provide dust collector of sufficient capacity to control the emissions.

b) Standards for Stack Emissions:

1) SPM

Not to exceed

150 mg/Nm3

2) SO2

Not to exceed

1080 kg/day

(ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	12000.00	Ltrs/day
2	HSD	100.00	Ltrs/M

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No. Chimney Attached To	Height in Mtrs.
-----------------------------	-----------------

gi.	Western Committee of Committee	The state of the s	Company of the Compan	CONTRACTOR OF THE STATE OF THE	reconstruction and the second second	2004 CAN SANT DISCOVERS AS
120		Steam Boiler	Linuary Carrier A. B. Aller Assessed	Programs Seminaria Sentra de Cara de C	V	GOTO CASAC SARGERA CARS TRUES
36	The state of the s	oceam Doner	Proceedings of the Control of the Co		144.00	
86	Manager and Manager and Charles	Water the residence of the country and the Country of the property	A COLUMN TO THE PARTY OF THE PA	and the second of the second o	dimension of grant below the constraint	<i>(100), (100), (100), (100), (100), (100)</i>
u,	12	THERMIC FI	TIID IID AMDD	NT.	00.00	Charles and the second second
W	ala 🖴 💮 🛴 🗀 🗀 ala ala ala ala ala ala ala ala ala al	14111111111 P		LINO. I	1 36 00	
3	A STATE OF THE PROPERTY OF THE PARTY OF THE	A SENCENCE OF STREET, SALE SOURCE STREET, STRE	producer and a company of the content was a subject to the content of the content	the contraction of the second		No 10 (1)
120	4. 2	THERMIC FL	TIDUDATED	NTO	00.00	NAME OF STREET
Ωl		TITITION		UINOLZ	1 33.00	
nu	establica action (2007) (2007) (2004) (2004) (2007) (2007) (2007) (2007)		a management consequence solves and account and account of the	and the Control of th	I DESCRIPTION AND DESCRIPTION OF THE STREET	800/2007 FEBRUAR COMPANIE 1.3 C.

(iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.

(v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 am. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

#### (vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

## 6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 wheters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 65 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
  - Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

# 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

(ii) Treatment: - NIL

- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
  - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.

c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

#### 8. Industry shall comply with following additional conditions:

i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.

iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposalto dumping ground.

iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in

- the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- ix. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down-stream of theterminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 9. This Consent is issued pursuant to the decision of Consent Appraisal Committee meeting of Board held on 26.11, 2012.
- 10. The Capital investment of the industry is Rs. 12425 Lacs.

(Rajeev Kumar Mital) Member Secretary

To, M/s Lavino Kapur Cottons Pyt Ltd Plot no H-1, MIDC TARAPUR TAL.TARAPUR DIST.THANE -401506

Copy to :- RO Thane/SRO Tarapur-I :- They are directed to ensure compliance of consent conditions and report accordingly. CAO/Cess wing/Master file

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	1242505	005406	01 Oct 201	2 HDFC Bank
2	100	000116	06 Oct 201	2 HDFC Bank