

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 24010437/24020781

Fax : 24024068 / 24023516

Email : rohq@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Kalpataru Point, 2nd - 4th Fl.
Opp. Cine Planet Cinema,
Near Sion Circle, Sion (F)
Mumbai-400 022

MU-3174/11

MSIHC/Red/L.S.I

Consent No. BO/RO(HQ)/CO/CC-742

Date: 2/11/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

CONSENT is hereby granted to;

M/s. Mahanagar Gas Ltd
City Gate Station, Opp. Anik BEST Depot,
Sion, Mumbai - 400 022

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 30/04/2017
2. The Consent is valid for City Gate Station (Pumping Station) at Sion, Opp. Anik Best Depot, Mumbai - 400 022.
2. CONDITIONS UNDER WATER ACT:
 - (i) The daily quantity of trade effluent from the factory shall be Nil
 - (ii) The daily quantity of sewage effluent from the factory shall be 13.0 M³/day .
 - (iii) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids	Not to exceed	100	mg/l.
(2) BOD 3 days 27o C.	Not to exceed	100	mg/l.
 - (iv) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
 - (v) **Non-Hazardous Solid Wastes:** Nil
3. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under
The daily water consumption for the following categories is as under:

(i) Domestic purpose	...	15.00 CMD
(ii) Water gets Polluted & Pollutants are Biodegradable...		0.00 CMD
(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic	...	0.00 CMD
(iv) Industrial Cooling, spraying in mine pits or boiler feed	...	0.00CMD

4. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Conditions for D.G. Set

- Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
 - Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
 - Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
 - D.G. Set shall be operated only in case of power failure
- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

Standards for Stack Emissions:

1	SPM	Not to exceed	150.0	Mg/Nm ³
2	SO ₂	Not to exceed	3.0	Kg/Day

- (ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	HSD	30.00	Ltrs/hrs

- (iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	DG Set 250 KVA (2 Nos)	9.5 each

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

- (vi) Other Conditions:

- 1] The petroleum products should be pumped through the booster station which should be absolutely leak proof. At no stage of pumping, there should be leakage or spillage.
- 2] Proper design and operational aspects of the system should be provided to ensure that soil and ground water are not contaminated during the operation.
- 3] The Pumping station should be kept in good conditions all the year round with adequate maintenance. The hazardous waste generated in handling, storage and transport should be disposed off in accordance with Hazardous waste (Management & Handling and Transboundary Movement) Rules 2008 and amendments made thereto.
- 4] The project authority should prepare On-site & Off-site emergency preparedness plan based on detailed risk analysis.
- 5] The Industry should regularly monitor the emission of Volatile Organic Compounds particularly Benzene, Toluene and Xylene.
- 6] The industry should monitor ambient air quality regularly from MoEF approved laboratory.
- 7] Monitoring of ground water (through piezometric wells) and soil at appropriate places at regular interval (every 3 months) should be carried out to ascertain that these are not getting polluted while operating the booster station.
- 6] The industry should not cause any nuisance in surrounding area.

5. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below:


Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	5.1 Used Oil/Spent Oil	24.57	Kl/annum	CHWTSDF
2	18.2 Spent Carbon	0.131	Ton/annum	CHWTSDF
3	33.3 Discarded containers of Ethyl Mercaptan	0.396	Ton/annum	CHWTSDF
4	35.1 Used Filters	1.147	Ton/annum	CHWTSDF
5	-- Cotton Waste	0.74	Ton/annum	CHWTSDF
6	-- Ekopearl	0.03	Ton/annum	CHWTSDF

- a. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- b. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

6. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
 - vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
 - vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
 - viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
 - ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
 - x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
 - xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down-stream of the Terminal manholes. No effluent shall find its way other than in designed and provided collection system.
 - xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
8. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the transmission and distribution process connected to it shall be stopped.
 9. This consent shall not be construed as exemption from obtaining necessary NOC from any other Government agencies as may deem fit necessary.
 10. The applicant shall submit a Bank Guarantee of Rs.05,00,000/- (Rupees five lacs only) to the Regional Officer MPCB, Mumbai within 15 days period from the date of issue of the consent, for compliances of consent conditions
 11. The Capital investment of the industry is Rs. 1240.0 Lacs.


 (Rajiv Kumar Mital, IAS)
 Member Secretary

To,
 M/s. Mahanagar Gas Ltd
 City Gate Station, Opp. Anik BEST Depot,
 Sion, Mumbai - 400 022

Copy to:

- a. RO- Mumbai /SRO-Mumbai-I
- b. CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	250100/-	883078	02 Dec 2011	Union Bank of India
2	3,50,000/-	670586	23/10/2012	United Bank of India