MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 24010437/24014701/24020781

24024068/24023516 Website: http://mpcb.gov.in.

E-Mail: jdair@mpcb.gov.in



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Rd. No.8 Opp Sion Circle, Sion (East). Mumbai-400 022.

RED/LSI

Consent No. BO/JD(APC)/EIC No. NG-7614-12/R/CC-430 Date:06 12 2012 Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Trans Boundary Movement) Rules 2008. [To be referred as Water Act, Air Act and H W (M, H & TM) Rules respectively].

CONSENT is hereby granted to:

M/s Team Ferro Alloys Pvt.Ltd. (Biomass based Power Plant), Plot No.B-17-20,B-20/1,21, MIDC Mundipar, Tal & Dist-Gondia.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of H W (M, H & TM) Rules subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period up to - 31.07.2015. 1.

2. The Consent is valid for the manufacture of:-

Sr. No. **Product**

Maximum Quantity Electricity Generation 8.0 MW

1) (Biomass based Power Plant)

3. CONDITIONS UNDER WATER (Prevention and Control of Pollution) ACT, 1974:

- (i) The quantity of trade effluent from the factory shall not exceed 75.0 m³/day.
- (ii) The quantity of sewage effluent from the factory shall not exceed 4.0 m³/day.
- (iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards.

The industrial effluent arising from various sections of Power Plant shall be given such treatment either collective or individually as the site condition permits that the final quality of effluent shall have following character standards:

a) Condenser Cooling Water:

рН 1) 6.5 to 8.5 Between 2) Temperature Not to exceed 5 Degree C. Higher than the intake water temperature.

3) Free available Chlorine Not to exceed 0.5 mg/l

b) Boiler Blow down:

1)	Suspended Solids	Not to exceed 100 mg/l
2)	Oil & Grease	Not to exceed 20 mg/l.
3)	Copper (Total)	Not to exceed 1 mg/l
4)	Iron (Total)	Not to exceed 1 ma/l

c) Cooling Tower Blow down:

1)	Free available Chlorine Not to exceed 0.5 mg/l.
2)	Zinc Not to exceed 1 mg/l
3)	Chromium (Total) Not to exceed 0.2 mg/l
4)	Phosphate Not to exceed 5 md/L

d) D.M. Plant Effluent:

1)	PH	Between	5.5 to 9
2)	BOD 3 days 27 Deg. C.	Not to exceed	
3)	COD	Not to exceed	250 mg/l
4)	Suspended Solids	Not to exceed	100 mg/l
5) E)	Oil & Grease	Not to exceed	10 mg/l
6)	TDS	Not to exceed	2100 mg/l

- (iv) Trade Effluent Disposal: The total treated effluent shall be recycled/reused for ash handling and dust suppression etc and industry shall achieve zero discharge.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards

(1) Suspended Solids Not to exceed 100 mg/l.
(2) BOD 3 days 27 C Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be recycled/ reused for ash handling and dust suppression etc.
- (vii) Non-Hazardous Solid Wastes:

Sr.No. Type of waste Quantity Treatment Disposal

1) Ash 40 MT/day --- Should be send to cement Manufacturer & dispose as per Govt of India Guidelines / Notification, vide No. SO 763(E), dtd 14-09-1999.

(viii) Other conditions:

a) The industry should monitor effluent quality regularly.

b) Green Belt a forestation shall be done up to 33% on available open space land.

c) The firm shall provide continuous flow meter for the measurement of the flow of the effluent.

d) Industry shall adopt clean technology like ozonization for cooling water treatment.

e) Industry shall provide dry fly ash handling & collection system and utilize the fly ash as per the fly ash notification of the Govt. of India.

f) Transportation of coal & fly ash shall be by closed system. Conveyor system wherever possible.

- g) Fly ash shall be 100% utilized within six years as per fly ash Notification.
- 4. The applicant shall comply with the provisions of the Water (Prevention Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under: The daily water consumption for the following categories is as under:

(i) Domestic ... 5.0 CMD.
(ii) Industrial Process generating ...} 25.0 CMD.
Bio-degradable waste water

(iii) Industrial Process generating ...} ... CMD Non-biodegradable waste water

(iv) Cooling water, Boiler, DM Plant, ...} 800.0 CMD (v) Gardening 10.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act which is also available on MPCB website at http://mpcb.gov.in/images/cessform1.pd

5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of Emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards

Standards for Emissions of Air Pollutants:

				/T											
									o e						
													mg		
)														
									Эε						
													27		

(ii) The applicant shall observe the following fuel patter:

w		A CONTRACTOR	Carl House Control	Administration of		noor of excellential		
	<u>Sr.</u> No.	100	Type:	of Eme	v I	\sim	100000000000000000000000000000000000000	
	PO 1900 DINE SHERISHMON	to are some	- YPC		-(1)	W I	uantity	
W	(i)	s Militar de la Maria de la 180	D.C.			AND THE PERSONS	14-24 A Superson Contract Cont	Santa 1
	t_{M}	4.0	Rice r	IUSK	Carl Salar	77 mil &	13 MT/c	law
W	(77V)	Control Owners	~		100			
4.7	(11)	Mary Mary Company	Coal 8	k Dola	char	20	Ton/da	~
W	reger to the second	1 200	\$102002 HE AND CO.			, <u>U</u>	i uinu	⊐ Y ∷
W.	(111)		VVood	Barrell Const.	100	10	8 4 T / - 1 -	Cute to
m	2000 (2001)		Marion Company			IU	MT/da	V
100	\$65503030300000000		2413436.04107.033.000	88 3 22 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	62011/2032/Jones 32/86/9/10	24.00	SECURE SECURE SECURE SECURE	All trommers

(iii) The applicant shall erect the chimney(s) of the following specifications:-

	Sr. No.	1000	Chimne	y attach	A4 4A				
	Section of the Language	and grant of	CONTRACTOR OF THE PROPERTY OF THE PARTY OF T	Arts, 1980 CONTRACTOR VINCENCY CO.	<u>eu (u</u>	6.540 (77.00)	He	ight in N	∕ltrs. ∗
37	1)	100	Boiler	and the second		W. W.		60	POWER TO BE
M	ii)	Surger St.	DCC	. /4 4551	2011	a contract of	ں , .	J.U	ence of the property
	•17	Appellation of		e(1x125 l	ΛVA) -	Company of the	2	5*	
W	100	a de la company	(*Ahove	"roof ton	A	Transcorpt Programme			

(*Above roof top of the building in which it is installed)

(IV) Control Equipment:

Electrostatic Precipitator provided to Boiler and dust suppression system provided to any other sources of particulate emission shall be operate and maintain continuously so as to ensure that TPM emission do not exceed 100 mg/Nm³

2. There shall not be any fugitive emission from bagasse handling and fly ash handling.

Conditions for DG Sets: -

1. Noise from DG Sets shall be controlled by providing acoustic enclosure or by treating the room acoustically

- Applicant should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room shall be designed for minimum 25 dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB(A) shall also be provided. The measurement of insertion loss shall be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- The Applicant should make efforts to bring down noise level due to DG Set, outside the premises, with ambient noise level requirements by proper setting and control measures.
- 4. Installation of DG Set must be strictly in compliance with recommendations of DG set manufacturer.
- 5. A proper routine and preventive maintenance procedure for DG Set shall be set and followed in consultation with the DG manufacturers, which would help to prevent noise levels of DG Sets from deteriorating with use.
- 6. The DG set shall be operated only in case of power failure. The applicant shall make arrangement for regular electrical power.
- 7. The Applicant shall not cause any nuisance in the surrounding area due to operation of DG sets.
- 8. In case of problems, the D.G. set shall not be operated until it is set back to satisfactory position.
- (V) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted / displayed to facilitate identification.

(VI) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(VII) Other Conditions:

- The Biomass & Coal handling system shall be covered with proper hooding and ventilation arrangements connected to dust suppress agent so as not to allow any fugitive emissions
- A separate environment monitoring cell with suitable qualified staff should be set up for implementation of the stipulated environmental safequards.
- 3 The industry shall not cause any nuisance in surrounding area
- 4. The industry shall monitor stack emissions & ambient air quality regularly
- 5. The applicant shall install online continuous monitoring system for stack emission analysis & same shall be directly connected to MPCB website http://mpcb.gov.in as well as to the respective Regional Office.
- 6. The applicant shall install one continuous automatic ambient air and micrometeorological monitoring station at location indicated by State Board to be set up and operate at its own cost measure SO₂ NO₂ and particulate matter. These CAAQMS shall also have necessary provision of networking to the Air Quality Monitoring network of MPCB.
- If due to any technological improvements or otherwise this Board is of opinion that all or any of the conditions referred above require variation (including the change of any control equipment either in whole or in part), this Board shall after giving the applicant an opportunity of being heard very all or any of such conditions and thereupon the applicant shall be bound to comply with the conditions so varied.

6. CONDITIONS UNDER HW (M, H &TM) RULES, 2008:

(i) The applicant shall handle hazardous wastes as specified below

		iazai dous wasies a	s specified below		Control of the Contro
Sr.	Item No. of Process g	enerating i Type of	Waste Quan	tity Dioce	
NIA	W/A/ 66 56- Osted 1-1		"" Quan	tity Dispo:	Sal
INU.	HW as per Schedule-I	10 miles			
1 1	5.2	2.2.21		200 C 100 C	100 MW 10
1	· · ·	spent/u	sea on - 250 m	t/annum Bv sal	e to authorized
	and the second second			and the second s	Control of the Contro
	A STATE OF THE STA	1.32 P		reproc	essor

- (ii) The authorization is hereby granted to operate a facility for collection, storage, transport, and disposal of hazardous waste.
- 7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services Department of Explosives, Inspectorate of factories and Local Body. In case of failure of pollution control equipments, the Production process connected to it shall be stopped.

8. General conditions:

- (i) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no of trees surviving as on 31st March of the year and no of trees planted by September end
- (ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant—and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise control production to abide by terms & conditions of this consent regarding pollution levels.
- Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- (vi) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- (vii) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises
 - 9. Applicant shall ensure to implement mitigation measures mentioned in Environment Management Plan
 - 10. The applicant shall make an application for renewal of the consent at least 60 days before the date of expiry to the consent.
 - 11. This consent is issued pursuant to the decision of Consent Committee meeting of Board held on 30 11 2012.
 - 12. The applicant shall submit the irrevocable operational bank guarantee of Rs.2.0/- Lacs drawn in favour of RO MPCB Nagpur within 15 days valid for one year period, towards compliance of the consent conditions and operation and maintenance of Pollution control system so as to achieve the consented standards.
 - 13. Total capital investment of the project is Rs.29.6/- Crore.

For and on Behalf of the Maharashtra Polixtion Control Board.

(Rajeev Kumar Mital, IA Member Secretary

To, M/s Team Ferro Alloys Pvt.Ltd. (Biomass based Power Plant), Plot No.B-17-20,B-20/1,21, MIDC Mundipar,Tal & Dist-Gondia.

Copy to:

- 1) Regional Officer, MPC Board, Nagpur2) Sub Regional Officer, MPC Board, Bhandara.

 They are directed to obtain bank guarantee from the industry as per consent condition no 12 and submit the compliance of consent conditions within one month's period with all monitoring results.
- 3) Chief Accounts Officer, MPC Board, Mumbai.

Received Consent fee of -

 Amount
 D.D.No.
 Date
 Drawn on

 Rs. 2,25,000/ 838999
 10.07.2012
 SBI

 Rs. 25,000/ 047435
 05.12.2012
 SBI

4) Cess Branch, MPC Board, Mumbai. 5) Master file.