MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701 Fax: 24024068 / 24023516 Website: http://mpcb.gov.in E-mail: mpcb@vsnl.net	NANARASHI RA	Kalpataru Point, 2 nd - 4 th Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.
--	--------------	--

RED/LSI
Consent No. BO/JD(APC)/EIC No. NK-12564-12/R/CO-(A(-1813 Date: 182/201

Consent to **Operate** under Section **26** of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Trans Boundary Movement) Rules 2008.

[To be referred as Water Act, Air Act and H W (M, H & TM) Rules respectively].

CONSENT is hereby granted to

M/s Maharashtra State Power Generation Co.Ltd. Nashik Thermal Power Station, P.O. Eklahare, Dist-Nashik.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of H W (M, H & TM) Rules subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to 31.12.2013.
- 2. The Consent is valid for the manufacture of:-

Sr. No.	Product	Maximum Quantity
1	Electricity Generation [from operation of Unit no.3,4 and 5]	630 MW [3 x 210MW] [4415MUs per year on 80% PLF]

[Unit 1 & 2 of 125 each has been decommissioned w.e.f. 1.07.2011]

- 3. CONDITIONS UNDER WATER (Prevention and Control of Pollution) ACT, 1974:
- (i) The quantity of trade effluent from the factory shall not exceed 31210 m³/day.
- (ii) The quantity of sewage effluent from the factory shall not exceed 2500 m³/day.
- (iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

The industrial effluent arising from various sections of Power Plant shall be given such treatment either collective or individually as the site condition permits that the final quality of effluent shall have following character standards:

Condenser Cooling Water: a)

••••		D - 4 a.m	6.5 to 8.5
1)	nΗ	Between	0.5 10 0.5
17	Pi i	Not to aveco	d 5 Degree C.
2)	Temperature	MOL TO EXCEE	d 5 Degree o.

Higher than the intake water temperature.

Free available Chlorine 3)

Not to exceed 0.5 mg/l

Boiler Blow down: b)

	Diotr dotti	Not to exceed	100	ma/l
1)	Suspended Solids	Not to exceed	100	1119/11
2)	Oil & Grease	Not to exceed	20	mg/l.
,	Copper (Total)	Not to exceed	1	mg/l.
3)	• •	Not to exceed	1	mg/l.
4)	Iron (Total)	1,00,00 0,000		•

Cooling Tower Blow down: c)

COOL	ing lower blow down.	N-44- avacad	0.5	ma/l.
1)	Free available Chlorine	Not to exceed	0.5	mg/i.
2)	Zinc	Not to exceed	1	mg/l.
,	Chromium (Total)	Not to exceed	0.2	mg/l.
3)		Not to exceed		ma/l.
4)	Phosphate	1101 10 020000	•	

D.M. Plant Effluent: d)

D.IVI.	Plant Emuent.		5.5 to 9
1)	PH	Between	
2)	BOD 3 days 27 Deg. C.	Not to exceed	30 mg/l. 1
3)	COD	Not to exceed	250 mg/l.
,	Suspended Solids	Not to exceed	100 mg/l.
4)		Not to exceed	10 mg/l.
5)	Oil & Grease	Not to exceed	2100 mg/l.
6)	TDS	NOT TO EXCECT	

- Trade Effluent Disposal: The total treated effluent shall be recycled/ reused 6) for ash handling, Coal handling, dust suppression etc to the maximum extent (iv) and remaining shall be utilized for plantation/gardening.
- Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate (v) and maintain the same continuously so as to achieve the quality of treated effluent to the following standards:

Suspended Solids (1)

Not to exceed

mg/l. 100

BOD 3 days 27 C. (2)

Not to exceed

100 mg/l.

- Sewage Effluent Disposal: The treated domestic effluent shall be recycled/ (vi) reused for ash handling, Coal handling, dust suppression etc to the maximum extent and remaining shall be utilized for plantation/gardening.
- Non-Hazardous Solid Wastes:-(vii)

		Quantity	Treatment Disposal
Sr.No	Type of waste	Quantity	Shall be send to Cement Manufacturer.
1	Fly ash/ Bottom	93240	Shall be send to Certent Mandidotars.
	Ash	MT/Month	Dispose as per Govt. of India Guidelines
2	Bottom Ash	23310 MT/Month	Notification vide no. SO 763(E)dated
3	Ash Sludge	400 MT/Month	14.9.1999.
4	Metal Scrap	20 MT/Year	By Sale

Other conditions:

- The industry should monitor effluent quality regularly. a)
- Green Belt a forestation shall be done up to 33% on available open space land.
- The firm shall provide continuous flow meter for the measurement of the flow of the b) c) effluent.
- Industry shall adopt clean technology like ozonization for cooling water treatment. d)
- Industry shall provide dry fly ash handling & collection system and utilize the fly ash as e) per the fly ash notification of the Govt. of India.
- Transportation of coal & fly ash shall be by closed system, Conveyor system wherever f)
- Fly ash shall be 100% utilized as per fly ash Notification. g)

4. The applicant shall comply with the provisions of the Water (Prevention Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under:

The daily water consumption for the following categories is as under:

ine c	ally water consumption to		6980	CMD.
(i)	Domestic			
		}	6510	CMD
(ii)	Industrial Process		44,700	CMD
(iii)	Cooling water Boiler,	}	44,700	•
(111)	E: Einhtime & Cordoning	}		CMD
(IV)	Fire fighting & Gardening	,		

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act which is also available on MPCB website at http://mpcb.gov.in/images/cessform1.pdf

5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

(I) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of Emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Standards for Emissions of Air Pollutants: A)

Stanu	arus ioi Eiiiio		100	mg/Nm³
(i)	SPM/TPM	Not to exceed		
(ii)	SO ₂	Not to exceed	138.	0MT/day
` '	NH ₃	Not to exceed	50 p	pm 🗼
(iii)	NO _x	Not to exceed	150	mg/Nm³
(iv)	NO _x	(v/v at 15% excess oxyg	gen)	

Conditions for D.G. Set:-B)

Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 2] dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6

Industry should make efforts to bring down noise level due to DG set, outside a.m. industrial premises, within ambient noise requirements by proper sitting and 41 control measures.

Installation of DG Set much be strictly in compliance with recommendations 51 of DG Set manufacturer.

A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.

D.G. Set shall be operated only in case of power failure. 7]

The applicant should not cause any nuisance in the surrounding area due to 81 operation of D.G. Set.

(II) The applicant shall observe the following fuel pattern:-

Sr. No. Type of Fuel		Quantity
Sr. No.		10,500T/day
	Coal	40 KL/day
2	Furnace Oil	10 KL/day
3	LDO	1.35 KL/D
4	Diesel	

(Coal should have max.34% ash & 0.5% sulphar content and attempt shall be made to reduce ash content to 29%)

(III) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No		<u>Height in Mtrs</u> .
i)	Unit III ,IV & V	92.5 each
ii)	DG Set (1x212.5 KVA)	3.5*
iii)	DG Set (2x412.5 KVA)	4.0*
''' <i>)</i>	(* Above roof top of the building i	n which it is installed)

(IV) Control Equipment:

- 1. Electrostatic Precipitator of sufficient capacity provided to each Boiler(1 to 7 nos) and any other sources of particulate matter shall be operate and maintain so as to ensure that TPM emission do not exceed 100 mg/Nm³
- Dust collection system and automatic water sprinkler system provided to Coal Handling Plant shall be operate and maintain continuously.
- 3. Dust collector of sufficient capacity provided to coal crusher and any other sources of SPM shall be operate and maintain continuously.
- 4. There shall not be any fugitive emission from coal storage yard.
- 5. The industry shall make necessary provisions for installing FGD with 90 % efficiency in its design and layout ad sufficient floor space so that it can be installed in future, as & when directed by Board.
- (V) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted / displayed to facilitate identification.
- (VI) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(VII) Other Conditions:

- 1. The coal handling system shall be covered with proper hooding and ventilation arrangements connected to dust suppress agent so as not to allow any fugitive emissions.
- 2. A separate environment monitoring cell with suitable qualified staff should be set up for implementation of the stipulated environmental safeguards.
- 3. The industry shall not cause any nuisance in surrounding area.
- 4. The industry shall monitor stack emissions & ambient air quality regularly.
- 5. The applicant shall install online continuous monitoring system for process stack emission analysis & same shall be directly connected to MPCB website http://mpcb.gov.in as well as to the respective Regional Office within 3 months period and operate the same regularly.
- 6. The applicant shall install three continuous automatic ambient air and micrometeorological monitoring station at location indicated by State Board to be set up and operate at its own cost measure SO₂, NO_x and particulate matter. These CAAQMS shall also have necessary provision of networking to the Air Quality Monitoring network of MPCB.
- 6. If due to any technological improvements or otherwise this Board is of opinion that all or any of the conditions referred above require variation (including the change of any control equipment either in whole or in part), this Board shall after giving the applicant an opportunity of being heard very all or any of such conditions and thereupon the applicant shall be bound to comply with the conditions so varied.

CONDITIONS UNDER HW (M &H) RULES, 1989 & AMENDMENT RULES, 2003: 6.

The applicant shall handle hazardous wastes as specified below: (i)

ihe	applicant shall handle	nazardous wastes as specific	<u> </u>	Disposal
Sr.	Item No. of	Type of Waste	Quantity	Dishosai
No.	Process			
INO.				
	generating HW as			
	per Schedule-I		50 MT/Yr	Sale to
1	5.1	Used/spent oil	50 WH7 H	authorized
	i			
				recycler/re-
				processor
 _		Waste/residues containing	5 MT/Yr	
2	5.2			CHWTSDF,
		oil (Oil filter)	I was a still a set	Butibori
3	34.3	Chemical sludge from	Irrespective of	Dulipon
		waste water treatment	any quantum	2000
-	22.2	Discarded	300 Nos/Yr	Authorised
4	33.3	barrels/containers		Re-
		parreis/containers		conditioner by
				MPCB
				INITOD

- The authorization is hereby granted to operate a facility for collection, storage, (ii) transport and disposal of hazardous waste.
- Whenever due to any accident or other unforeseen act or even, such emissions occur 7. or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of factories and Local Body. In case of failure of pollution control equipments, the Production process connected to it shall be stopped.

General conditions: 8.

The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September (i) every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.

The applicant shall provide for an alternate electric power source sufficient to operate (ii) all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

The firm shall submit MPCB, the Environmental Statement Report for the financial year (iii) ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.

The applicant shall install a separate meter showing the consumption of energy for (iv) operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.

Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with (v) arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down-stream

of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- (vi) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- (vii) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 9. Applicant shall ensure to implement mitigation measures mentioned in Environment Management Plan.
- 10. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- 11. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 12. The applicant shall comply with the recommendations of the Task Force for implementation of CREP recommendations for Thermal Power Plants.
- 13. The applicant shall implement mechanical close type transportation system for coal & mineral metal transporting trucks.
- 15. The applicant shall submit the irrevocable fresh Bank Guarantee of Rs. 120/-Lakhs as mentioned in the following table to achieve the consented standards/conditions mentioned in action plan. The above BG shall be drawn in favor of RO, MPCB, Nashik & submit within 15 days to RO, MPCB, Nashik, valid for one year period.

Sr No	Issues	Work to Done to achieve the standard	Unit No	MPCB Remarks	Bank Guarantee (BG) Imposed
1	Revamping	R & M of ESP	3	Renovation & Modernization of plant shall be completed and commissioned on or before 31.12.2013.	Shall Submit the B.G. of Rs.30 lakhs towards
	27		4	Unit -4 ESP augmentation and Renovation & Modernization shall be completed and commissioned on or before 31.12.2013.	compliance of Sr. No.1,2 & 3.
			5	Unit -5 ESP augmentation and Renovation & Modernization shall be completed and commissioned on or before 31.12.2013.	
2	Raw material related like	-		NTPS shall use coal having ash content less than 34% continuously	
3	Pollution Control System at Coal Handling Plant	Providing of Dust collection system at coal crusher house.	Station	1. Dust extraction system at CHP II secondary crusher house shall be completed and commissioned on or before 31.12.2013.	

		automatic water sprinkling system in coal handling plant.		Fog / Mist generation system for W/T CHPI, W/T II and Stage II Bunker shall be provided and commissioned on or before 31.12.2013. Ammonia dosing conditioning	Shall submit	
	By Process Change	a. Flue gas conditioning system		system for unit-4 & 5 shall be provided on or before 31.12.2013.	the B.G. of Rs.30 lakhs towards	
5	Coal Storage / Yard	Providing of automatic water sprinkling system in coal storage yard	Station Automatic water sprinkling system shall be provided to Unit- 5 on or before 31.12.2013		compliance of Sr. No. 4 & 5.	
		2.Providing closed type stacker reclaimer	Station	Closed type stacker reclaimer shall be provided on or before 31.12.2013.		
		3. Procurement of compactor	Station	Compactor shall be provided on or before 31.12.2013.		
6	Water Pollution Issue	Providing of Effluent Treatment Plant	Station	Modification /up gradation of existing Effluent treatment plant of capacity 500 M3/ Hr - shall be provided on or before 31.12.2013.	Shall submit the B.G. of Rs.30 lakhs towards	
		Providing of Ash Water Recycling Pump House	Station	Commissioning of additional pipe line of waste water recovery to plant will be provided on or before 31.12.2013.	compliance of Sr. No 6, 7, & 8.	
7	Zero Discharge Concept	Enhancing recovery system	Station	01. Additional pipe line from WWR to TPS for augmentation of ash water recovery of ash bund shall be provided on or before 31.12.2013.		
			Station	02. Construction of additional three nos. circular settlers & settling tank and construction of ETP in place of phase-II pond and corresponding pipe lines shall be completed and commissioned on or before 31.12.2013.		
8	Dry Ash Collection System	Providing of ash collection facility	NTPS, U-3,4 & 5	shall be provided on or before 31.12.2013.		
9	Installation Of CAAQMS	Draft order for supply, installation and commissioning of one CAAQMS submitted to corporate office for approval.		or before 31.12.2013.	Rs.30 lakhs towards compliance of Sr . No.9,10,11 &	
10	Installation of Online Stack		3,4&	On-line opacity meters shall be installed and commissioned on or before 31.12.2013.	12	

				Total BG Rs.120 Lakhs
12	Providing of metallic roads	Construction of concrete road All work of construction of internal power house roads with fly ash concrete along with mechanical road sweeper shall be completed and commissioned on or before 31.12.2013.		internal power house roads with fly ash concrete along with mechanical road sweeper shall be completed and commissioned on or before 31.12.2013.
11	Fly ash utilization	85% Ash utilization	Unit 3,4 & 5	100 % ash utilization shall be done on or before 31.12.2013.
		Providing of separate Energy meters to ESP	3,4&5	Separate Energy meters shall be provided to ESP of unit no. 3, 4& 5 on or before 31.12.2013.
	monitoring	Providing of online SO2 & NOx meter to stack	3,4 & 5	On-line SOX/ NOX Analyzers to stack shall be installed and commissioned on or before 31.12.2013.

- This is issued pursuant to the decision of Consent Appraisal Committee meeting 16. of the Board held on 31.01.2013.
- The Total Gross Capital Investment of the industry is Rs. 714.09/- Crores. **17**.

For and On Behalf of the Maharashtra Pollution Control Board,

> (Rajeev Kumar Mikal, IAS) Member Secretar

To,

M/s Maharashtra State Power Generation Co. Ltd.,

Nashik Thermal Power Station,

P.O. Eklahare, Dist-Nashik.

1) Regional Officer MPC Board, Nashik / Sub Regional Officer, MPC Board, Nashik.

They are directed to submit the performance report along with the results and compliance of directions issued by Board within one month period. As per the decision taken in the CAC meeting held on 31.01.2013, obtain fresh BG of Rs.120 Lakhs as mentioned in the above table from the industry and submit the compliance report within a month.

2) Chief Accounts Officer, MPC Board, Mumbai.

Received Consent fee of -

Received Consent fee of -			Data	Drawn on	
Sr.No.	Amount	D. D. No.	<u>Date</u>	<u> </u>	
		070000	29.10.2012	Bank of Baroda	
1	Rs.1,00,000/-	679389	29.10.2012		

4) Cess Branch, MPC Board, Mumbai.

5) Master file.