MAHARASHATRA POLLUTION CONTROL BOARD

Phone

4010437/4020781

/4037124/4035273

Fax

24044532/4024068 /4023516

Email

enquiry@mpcb.gov.in

Visit At :

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Mumbai - 400 022

Red/L.S.I

Date: 17/04/2013

Consent No: Bo/JD-PAMS/EIC.NO-RD2505-13/R/CC/(A(-3323

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008
[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

Sudarshan Chemicals Industries Ltd Plot No-19-A/1 and 2, MIDC Mahad Raigad, Maharashtra Mahad-402309

India

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H). Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.07.2014.

G.

2. The Consent is valid for the manufacture of -

		7./T	HOM
Sr. No.	Product Name	Maximum Quantity	UOM
1	Pigments (Rithalo Blue/Green pigments, Organic pigments, inorganic pigments, Mica Pearl pigments	730	MT/M
. F	BY PRODUCTS		•
10.	Sulphuric Acid (15-25%)	2500	MT/M
2	Phosphoric Acid (12-15%)	600	MT/M
3	Chemical Gypsum (CaSO ₄)	600	MT/M
4	Aluminum Chloride (5- 15 %)	1500	MT/M
5	Recovered pigments	25.0	MT/M
6	Phosphoric Acid (30-35 %)	200	MT/M
7	Recovered Solvents	100	MT/M

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 4072.0M3.

(ii) The daily quantity of sewage effluent from the factory shall not exceed 141.0M3.

5	Boiler Soot/Incinerator Ash (ash generated by burning	500.00	Kg/Annum	Sale/recycle for making Cow dung cakes/CHWTSDF
6	Insulating Material	1000.00	Kg/Annum	Sale/Recycle/ Return to Vendor, CHWTSDF
7	Excess Biomass from ETP	200.00	Kg/Annum	Used as Bio Fertilizer/compost

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess amendment Rules, 2003 there under

The daily water consumption for the following categories is as un 172.00

(i) Domestic purpose

(ii) Water gets Polluted & Pollutants are Biodegradable ...

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ...

(iv) Industrial Cooling, spraying in mine pits or boiler feed

35.00 CMD

CMD

 $5.00~\mathrm{CMD}$ CMD 41.0

(vi) Gardening/Plantation The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

shalf install a comprehensive control system The applicant consisting of control equipments as is warranted with reference to (i) generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment:

ndustry shall provide dust collector/scrubber of sufficient capacity to control the emissions.

ions for D.G. Set

a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

	10 00 0001110		
1) 2) 3) 4) 5) 6) 7) 8) 9) 10) 11) 12) 13) 14) 15)	pH Suspended Solids BOD 3 days 27 deg. °C COD Oil & Grease Mercury (as Hg) Hexavalent (as Cr) Chromium (Total Chromium Copper (as Cu) Zinc (as Zn) Nickel (as Ni) Cadmium (as Cd) Chloride (as Cl) Sulphate (as SO4) Phenolic Compounds (as	Between Not to exceed	6.0 to 8.5 100 mg/I. 100 mg/I. 250 mg/I. 10 mg/l. 0.01 mg/l. 0.1 mg/l. 2.0 mg/l. 3.0 mg/l. 3.0 mg/l. 1000 mg/l. 1000 mg/l. 1000 mg/l. 1000 mg/l.
		Not to exceed	
16)	Bio-assay Test (with 1:8 dilution of effluent)	Not to exceed	90% survival of Test animals after 96 hours.

- (iv) Trade Effluent Disposal: The treated industrial effluent shall be segregated and reused back into process to maximum extent and remaining treated effluent shall be send to CETP for further treatment & disposal. There should not be any discharge of effluent outside factory premises.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.
(2)	DUD Q ways 210 C.			

Effluent Disposal: The treated domestic effluent shall be soaked in a pit, which shall be got cleaned periodically. Overflow, if any, shall be used and for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

G N	T Of Wasto	Quantity	UOM	Disposal
Sr. No.	Type Of Waste Paper/Canteen Waste	3600.00	Kg/Annum	Composting
2	Mica Waste	1800.00	MT/A	Sale/CHWTSDF
3	Rubber, Hand Gloves, PVC shoes, Tarpoline, Paper Bags	1000.00	Kg/Annum	Recycle/Sale after decontamination
4	Broken Discarded Glass	500.00	Kg/Annum	Sale after decontamination

- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

b. Standards for Emissions of Air Pollutants;

	C No Parameters Standards				
S.No	Parameters				
1	SPM/TPM	Not to exceed	150.0	mg/Nm³	
2	SO ₂ (boiler for coal as fuel))	Not to exceed	340	kg/day.	
3	SO2 (boiler for LDO as fuel))	Not to exceed	36.0	kg/day	
4	SO ₂ (for F.O as fuel))	Not to exceed	504	kg/day	
4		Not to exceed	20	mg/Nm ³	
5	HCl		5.0	mg/Nm³	
6	Cl_2	Not to exceed			
7	NH ₃	Not to exceed	30.0	mg/Nm³	

(i) The applicant shall observe the following fuel pattern:-

Quantity	UOM
	MT/day
	MT/day
	MT/day
	MT/day
	KL/M
	Quantity 34.00 54.00 1.00 14.00 2.50

(ii) The applicant shall erect the chimney(s) of the following specifications:-

	Chimney Attached To	Height in Mtrs.
Sr. No.		
1	Boiler-I & Boiler-II	36.00 Common for both boiler
2	Thermopack	23.00
3	Incinerator (for paper waste)	32.00
4	HCL Scrubber	20.00
5	Ammonia Scrubber	20.00
$\frac{5}{6}$	Chlorine Scrubber	20.00
7	DG Set (1000 KVA)	4.50 above the roof in which D.G is installed

M

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
 - (vi) Other Conditions:
 - 1) The industry should not cause any nuisance in surrounding areas
 - 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT) HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

			33946	
Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	5.1 Used /spent oil	1000.00	Ltt/A	To authorized party having actual user registration from MoEF/CPCB or sent to CHWTSDF
2	5.2 contaminated oil soak cotton	250.0	Kg/A	CHWTSDF
3	15.2 Discarded asbestos	1.20	MT/A	CHWTSDF
4	20.2 Spent solvents	50.00	Ltr/A	To authorized party having actual user registration from MoEF/CPCB or sent to CHWTSDF
5	33.3 Discarded containers/Liners	4500	Nos/A	Sale/recycler/CHWTSDF
6	34.3 Chemical sludge from waste water treatment	500.00	MT/A	CHWTSDF
7	33.1 Chemical-containing residue	0.10	MT/A	CHWTSDF
8	85.1 Filters and filter material which have organic liquid	1.00	MT /A	
9	35.3 Spent carbon	200.00	Kg/A	CHWTSDF

- (ii) Treatment: NIL
- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

7. Industry shall comply with following additional conditions

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
 vi. The applicant shall provide facility for collection of environmental samples and
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- vii The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules 1992.
- (Second Amendment) Rules, 1992.

 ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 8. If CETP does not work for achieving standards & problem of pollution occurs, industry shall voluntarily stop the production or total effluent shall be reused.
- 9. The consent should not be construed as any exemption from obtaining necessary NOC from other Govt. agencies as may deemed fit necessary.
- 10. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.
- 11. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant
- 12. The Industry shall submit Bank Guarantee of Rs. 5 Lakh towards 0 & M of the pollution control system. The same shall be valid up to consent period and shall be submitted at Regional Office MPCB Raigad within 15 days period.
- 13. This Consent is issued pursuant to the decision of CAC meeting of the Board 2013 held on 22/03/2013.
- 14. The Capital investment of the industry is Rs. 98.84 Cr.

15. This is issued as per the power delegated vide office Note dtd-09/4/2013.

(P.K.Mirashe)

Assistant Secretary (Technical)

To,

Sudarshan Chemicals Industries Ltd

Plot No-19-A/1 and 2 MIDC Mahad-402309

Raigad, Maharashtra

India.

Copy for information to:-

Regional Officer MPCB Raigad.

Sub-Regional Officer MPCB, Mahad

Chief Account Officer MPCB Mumbai

Descired Concept for of-

препотее от			
Amount(Rs.)	DD. No.	Date	Drawn On
	052604	14 Dec 2012	SBI
	506097	15 Nov 2012	SBI
		Amount(Rs.) DD. No. 150000 052604	Amount(Rs.) DD. No. Date 150000 052604 14 Dec 2012

Note:-Balance fee of Rs.1,77,496/- will be considered at the time of next renewal of Consent.