


# MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2 <sup>nd</sup> - 4 <sup>th</sup> Fl.
Fax: 24024068 / 24023516		Opp. Cine Planet Cinema,
Website: <a href="http://mpcb.gov.in">http://mpcb.gov.in</a>		Near Sion Circle, Sion (E)
E-mail: <a href="mailto:apac@mpcb.gov.in">apac@mpcb.gov.in</a>		Mumbai-400 022.

**Red/S.S.I**

**Date: 10/05/2013**

**Consent No: BO/JD(APC)/TB-2/EIC NoKP-11125-12/O/CC-4083**

**Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008**

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

**M/s. Synergy Green Industries Pvt. Ltd.,  
Plot No. C-18, Five Star MIDC Hatkanagale,  
Tal- Hatkanagale, Dist - Kolhapur.**

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to --- 31/05/2015.**
- 2. The Consent is valid for the manufacture of -**

Sr. No.	Product Name	Maximum Quantity	UOM
1	Engineering Casting ( CI & SG)	18000	MT/A

**3. CONDITIONS UNDER WATER ACT:**

- (i) The daily quantity of trade effluent from the factory shall be Nil.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 20.0 M<sup>3</sup>.

**(iii) Trade Effluent:**

(iv) Treatment: NA

(v) Trade Effluent Disposal: NIL

**(vi) Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

**(vii) Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vi) Non Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment Disposal
1	Slag & Ladle Skull	2	MT/D	Landfill
2	Sand Dust	4	MT/D	Landfill



(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic	...	25.00 CMD
(ii) Industrial Processing	...	0.00 CMD
(iii) Industrial Cooling	...	60.00 CMD
(iv) Agriculture / Gardening	...	15.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. **CONDITIONS UNDER AIR ACT :**

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. **Control Equipment:**

- i) Industry shall provide fume extraction system followed by wet scrubber of sufficient capacity to furnace and dust collector to all other sources of particulate emissions.
- ii) There shall not be any fugitive emissions.

**Standards for Emissions of Air Pollutants:**

- (i) SPM/TPM Not to exceed 150 mg/Nm<sup>3</sup>

(i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Electricity		

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Electric Induction furnace (2 nos.)	20
2	Knockout	22
3	Sand plant	12
4	Paint booth	12
5	Dedusting section	12
6	Classifire filter	11
7	DG Set ( 500 KVA)	3.5 above roof

(iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

**Conditions for DG Set :**

- (1) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- (2) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB(A) shall also be provided. The measurement of Insertion loss will be done at different points at 0.5 metres from acoustic enclosure/room and then average.
- (3) The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m. and night time is reckoned between 10 p.m. to 6 a.m.
- (4) Industry should make efforts to bring down noise level due to DG Set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- (5) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- (6) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- (7) The DG set shall be operated only in case of power failure.
- (8) The applicant should not cause any nuisance in the surrounding area due to operation of the DG set.

**6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:**


(i) The Industry shall handle hazardous wastes as specified below.

Sr. N.	Type Of Waste	Quantity	UOM	Disposal
1	5.2 Waste/ residue containing oil	1000	Litr/Yr.	CHWTSDF
2	33.3 Discarded containers/ barrels/ liners	1000	Nos/Yr.	Salv
3	21.1 Paint residue	3	MT/Yr.	CHWTSDF

(ii) Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure




of pollution control equipments, the production process connected to it shall be stopped.

b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.

c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

**7. Industry shall comply with following additional conditions:**

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste -- The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as per the provisions of rule 11 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the



pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.


xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

8. This is issued with the approval of Consent committee meeting held on 06/05/2013.

9. The Capital investment of the industry is Rs.42.53/-Crs.

10. Industry shall submit the Bank Guarantee of Rs. 5.0 lacs valid for one year at Regional Office Kolhapur within 15 days, towards provision of STP within six months i.e upto 31/10/2013.

11. This consent is issued as the empowerment granted vide office note dated 9/1/2013 (FTSE30112FT0030).

  
(V. M. Motghare) 9/5/13  
Joint Director (Air Pollution Control)

To,  
M/s. Synergy Green Industries Pvt. Ltd.,  
Plot No. C-18, Five Star MIDC Hatkanagale,  
Tal- Hatkanagale, Dist - Kolhapur.

Copy to:

RO- MPCB Kolhapur /SRO-MPCB Kolhapur

- They are directed to submit the detail report of air pollution control within 1 month period.

CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	Rs.2,25,100/-	829809	18/05/2012	Bank of Baroda