MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

E-mail: ast@mpcb.gov.in



Kalpataru Point, 2nd - 4th Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Red/SSI

Date: 23/01/2014.

Consent No. BO/AST/RO-KN/EIC No KN-5689-12/R/CC- 00704

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management , Handling & Transboundry) Rules

[To be referred as Water Act, Air Act and HW (M, H&TM) Rules

CONSENT is hereby granted to,

M/s. Herhert Brown Pharma & Research Lab., Plot No. W-256-257 A, 258A, Phase II, MIDC Dombivli,

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to 31/04/2016.
- 2. The Consent is valid for the manufacture of-



No.	Products	Quantity in Kg/m.
	2 Methylamino-5-Chlorobenzophenone	100
2	2- Amino 5- Chlorobenzophenone	500
3	Chlorocetamido 5- Chlorobenzophenone	100
14	Methyl Nicotinate BP	150
5	Chlorodizepoxide IP / BP / USP	350
6	Chlorodizepoxide Hydrochloride BP	40
7	Nordizepam	, 10
8	Benzyl Nicotinate	25
9	Diazepam IP / BP	300
10	Diethylamine Salicylate	100
11	Dichlofenec Sodium	100

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed $3.0\ m^3$.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed $0.8\ m^3$.

(iii) Trade Effluent:

<u>Treatment</u>: The applicant shall provide comprehensive treatment system consisting of primary/secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	рН	Between	6.5 to 8.5
2	Suspended Solids	Not to exceed	100 mg/I.
3	BOD 3 days 27 deg.0	Not to exceed	100 mg/I
4	COD	Not to exceed	250 mg/I.
5	Oil & Grease	Not to exceed	10 mg/l.
6	Total Dissolved Solids	Not to exceed	2100 mg/l.
7	Bio assay Test	90% survival of fish after 100% effluent**	first 96 hrs in
8	Sulphate	Not to exceed	1000 mg/l.
9	Chloride	Not to exceed	600 mg/l.
10	TAN	Not to exceed	50 mg/l.
11	Phenolic Compound	Not to exceed	01 mg/l.

- (iv) Trade Effluent Disposal: The treated trade effluent shall be recycled/ reused to the maximum extent and remaining shall be discharged to CETP.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards:

(1) Suspended Solids Not to exceed 100 mg/l. (2) BOD 3 days 27 Deg. C. Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes: NIL
- (viii) Other conditions: The industry should monitor effluent quality regularly from MoEF approved laboratory.
- The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under:

 The daily water consumption for the following categories is as under:

i	Domestic	1.00	CMD
ii	Industrial Processing	9.00	CMD
iii	Industrial Cooling / Boiler	5.00	CMD
iv	Agriculture/Gardening	2.00	CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
- Control Equipment: 1] Scrubber of sufficient capacity should be provided to reactor or any other sources of emissions to limit the gaseous emissions.

 2] Dust collector of sufficient capacity shall be provided to Pulverizer / Blender.

Conditions for D.G. Set:

- 1. Noise from D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provide. The measurement of insertion loss will be done at different points at 0.5 metres from acoustic enclosure/room and the average.
- 3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m. and night time is reckoned between 10 p.m. to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to D.G. set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- 5. Installation of D.G. set must be strictly in compliance with recommendations of D.G. set manufacturer.
- 6. A proper routine and preventive maintenance procedure for D.G. set should be set and followed in consultation with the D.G. manufacturer which would help to prevent noise levels of D.G. set from deteriorating with use.
- 7. D.G. set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. set.

Standards for Emissions of Air Pollutants:

1	SPM/TPM	Not to exceed	150	mg/Nm ³
2	SO_2	Not to exceed	7.9	Kg/Day
3	NH3	Not to exceed	50	ppm.
4	HCL	Not to exceed	35	mg/Nm ³
5	CI2	Not to exceed	03	ppm

(ii) The applicant shall observe the following fuel pattern:-

Sr Fuel Type		Quantity		
1	LDO	100 Ltr/d.		
2	Diesel	60 Lit/d.		

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Stack Attached To	APC System	Height in Mtrs.	Type of Fuel	Quantity & UoM	S %	SO ₂ Kg/Day
1	Boiler	**	30	LDO	100 Kg/d.	1.8	7.92
2	Process Reactor	Scrubber	13				
3	D.G. Set 500 KVA	Acoustic Enclosure	3*	HSD	60 Lit/d.	1.0	1.2

(* above the height of building where the DG set is installed)

meth.

- (iv) The applicant shall provide ports in the chimney/(s) and facilitates such as ladder, platform etc. For monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. And these shall be painted / displayed to facilitate identification.
- (v) The industry shall take adequate measures for control for noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. And 10 p.m. And night time is reckoned between 10 p.m. And 6 p.m.
- (vi) Other Conditions:
 - 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality regularly from MoEF approved laboratory.

6. CONDITIONS UNDER HW (M, H &TM) RULES, 2008

The applicant shall handle hazardous wastes as specified below:

Sr. No	Item No (Sch-I)	Type of Waste	Quantity	Disposal
. 1	34.3	Chemical Sludge from waste water treatment	10 Kg/m.	CHWTSDF

- Whenever due to any accident or release of gases or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emissions and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organizations as require under the law.
- 8. General conditions:
- (i) The applicant shall bring minimum 33% of the available open land under green coverage/plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- (iii) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm shall submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.
- (v) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption
 - designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.

 Separate drainage system shall be provided for collection of trade and sowers office to
- (vi) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down-stream of the terminal manholes. No effluent shall find its

way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

(vii) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

(viii) The industry shall ensure that fugitive emissions from the activity are controlled so as to

maintain clean and safe environment in and around the factory premises.

(ix) The applicant shall maintain good house keeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

- 09. If CETP dose not work for achieving standards & problem of pollution occurs, industry shall voluntarily stop the production or total effluent shall be reused.
- 10. The consent should not be construed as any exemption from obtaining necessary NOC from other Govt. agencies as may deemed fit necessary.
- 11. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.
- 12. This consent is issued as per industries request for plain renewal and refused the product mix change.
- 13. The industry shall submit the Bank Guarantee of Rs. 1 Lakh to RO Kalyan within 15 days, towards O & M and not to take any effective steps towards change in product mix. The Bank Guarantee shall be valid up to 31.08.2016.
- 14. This consent is issued as per the delegation of powers to HOD's vide Board Office Order No. 31/2013 dtd. 01/03/2013.
- 15. The capital investment for expansion is Rs 2.71 Crore.

(P. K. Mirashe) Asst. Secretary (Technical)

To, M/s. Herhert Brown Pharma & Research Lab., Plot No. W-256-257 A, 258A,Phase II, MIDC Dombivli, Dist. Thane.

Copy to:1) Regional Officer, MPCB, Kalyan & 2) Sub-Regional Officer, MPCB, Kalyan-I- They are to ensure the compliance of consent conditions.

3) Chief Accounts Officer, MPCB, Mumbai 4] Cess Branch, MPCB. 5] Master file.

Received Consent fee of -

 Amount
 D.D.No.
 Date
 Drawn on

 Rs. 75,000/ 613091
 23/12/2011
 Saraswat Co-op Bank

* The Consent fees of Rs. 10,000/- is remaining with the Board will be considered at the time of next renewal.