MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 4010437 / 4014701 /

4020781

Fax : 4024068 / 4023516 Website: http://mpcb.mah.nic.in. E-Mail : ast@mpcb.gov.in.



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Road No.8, Opp. Sion Circle, Sion (East) Mumbai-400 022.

Consent No. BO/AS(T)/EIC No. TN-3468-12/A/GEN-01555 Date: 17/02/2014.

Consent to Operate under Section 26 of the Water(Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules, 2008. [To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Alchemie Pharma Chem Pvt. Ltd., Plot No. L-10, MIDC Tarapur, Tal. Boisar, Dist. Thane-401 501

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period upto 31.12.2016. 1.

The Consent is valid for the manufacturing of-2.

he Consent is valid for the manufacture		Qty	
Sr.No.	4/1/	1,000 Kg/M	
1	Alpha-Picolinic Acid	100 MT/M	
2	Chromium Picolinate	1.000 Kg/M	
3	Zinc Picolinate	2,000 Kg/M	
4	Other Fine Chemicals	5,000 Kg/M	
5	Spent Nitric Acid (By product)	10 TPH	
6	Steam Generation		

- CONDITIONS UNDER WATER (Prevention & Control of Pollution) ACT, 1974:
- The daily quantity of trade effluent from the factory shall not exceed 4.0 m3/day. (i)
- The quantity of sewage effluent from the premise shall not exceed 5.0 m³/day.
- Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary/secondary and/or tertiary treatment as is warranted with (iii) reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards-

re the c	quality of treated endent to the	Between	5.5	to 9.0.
(1) (2) (3) (4) (5) (6) (7) (8)	pH Suspended Solids BOD 3 days 27 Deg. C. COD Oil & Grease Total Dissolved Solids Sulphates Chlorides	Not to exceed	100 100 250 10 2100 1000 600	mg/l. mg/l. mg/l. mg/l. mg/l. mg/l.
(13)				

- (iv) Trade Effluent Disposal: The treated effluent shall be recycled to the maximum extent and remaining, if any, shall be discharged into CETP.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards-

(1) Suspended Solids Not to exceed 100 mg/l.
(2) BOD 3 days 27 Deg. C. Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated sewage shall be soaked into soak pit which shall be got cleaned periodically. Overflow if any shall be disposed into CETP.
- (vi) Non-Hazardous Solid Wastes:

 Type of waste Quantity Treatment Disposal
 Coal Ash 4 Tons/day Sale to Brick Mfg. unit.
- (vii) Other Conditions: The firm shall monitor effluent quality regularly.
- 4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Amendment Rules 2003 thereunder:

The daily water consumption for the following categories is as under:

 (i) Domestic
 ...
 5.0 CMD

 (ii) Industrial
 ...
 3.0 CMD

 (iii) Industrial Cooling/Boiler
 ...
 80.0 CMD

 (iv) Gardening
 ...
 2.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the CESS as specified under Section 3 of the said Act.

CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment:

- a) The firm shall provide dust collectors followed by wet scrubber to coal fired boiler to control air pollution and O&M it round the clock.
- b) The firm shall provide scrubbers of sufficient capacity to control air pollution wherever necessary and O&M it round the clock.
- c) The firm shall not cause any nuisance in surrounding due to fugitive emission.
- (ii) Standards for Emissions of Air Pollutants:

(i) SPM/TPM Not to exceed 150 mg/Nm³ Not to exceed 120 Kg/day

(iii) The applicant shall observe the following fuel pattern:-

 Sr.No.
 Type of Fuel
 Quantity

 1.
 Coal
 12 MT/day

 2.
 HSD
 30 Ltrs/day

(iv) The applicant shall erect the chimney(s) of the following specifications:-

Sr.No. Chimney attached to
1. Boiler(10 TPH)

Poller(6 TPH Standby)

APCS Provided

Height in Mtrs.

30 mtrs.

Boiler(6 TPH-Standby) } by Wet scrubber }
 D.G. Set (125 KVA) -- 2 mtrs above roof.

(v) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for

- use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.
- (vi) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and

(vii) Other Conditions:

1) The firm shall not cause any nuisance in surrounding area.

6. CONDITIONS UNDER HW (M&H) RULES, 1989 & AMENDMENT RULES, 2003:

(i) The applicant shall handle hazardous wastes as specified below:

Sr. No.	Item No. Of process substance generating HW as per Schedule-I/II	Type of waste	Quantity	Disposal
1	28.1	Residues & Wastes	20 Kg/M	CHWTSDF
2	34.3	ETP Sludge	102	

7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Pactories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. General conditions:

(i) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.

(ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution level.

(iii) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

(iv) The firm shall submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.

(v) The applicant shall install a separate meter showing the consumption of energy for operation of domestic effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption alongwith Environmental statement.

(vi) Separate drainage system shall be provided for collection of sewage effluents. No effluent shall find its way other than in designed and provided collection system. Neither storm