# MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 24010437/24014701/24020781

: 24024068/24023516 Website: http://mpcb.gov.in. E-Mail: jdair@mpcb.gov.in



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Rd. No.8, Opp. Sion Circle, Sion (East),

Mumbai-400 022.

RED/LSI

Consent No: BO/JD(APC)/EIC No.CH-1479-13/O/CC-6750

Date: 18 /07/2014

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorisation / Renewal of Authorisation under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry) Rules , 2008. [To be referred as Water Act, Air Act and HW (M,H & TM) Rules respectively].

CONSENT is hereby granted to,

M/s. Western Coal Fields Ltd, Nandgaon Incline, WCL Chandrapur Area, Po. Nandgaon (Pode), Tal & Dist. -Chandrapur.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- The Consent to Operate is granted for a period up to 31/03/2017 or up to 1. validity of mine lease period whichever is earlier.
- lid for the activity of Mining over a mining lease area of 128 ha. 2.

The Consent	is valid for the activity	Of Willing Over a liming fountity
Sr.No.	Product	Maximum Quantity 0.30 Million Tones/Year
1)	Coal	0.30 Willion Tones/Tear

- CONDITIONS UNDER WATER ACT: 3.
  - The daily quantity of trade effluent from the factory shall not exceed 6508.0 m<sup>3</sup>. (Including Mine Discharge).
  - (ii) The daily quantity of sewage effluent from the factory shall not exceed 78.0 m<sup>3</sup>.
  - (iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

as to a	crileve the quality of the areas	Between	5.5 to 9	9.0
1) 2) 3) 4) 5) 6) 7) 8)	pH Suspended Solids BOD 3days 27 Deg. C. Oil & Grease Total Dissolved Solids Chlorides Sulphate Nitrate Nitrogen Phenolic	Not to exceed	100 30 10 2100 600 1000	mg/l. mg/l. mg/l. mg/l. mg/l. mg/l. mg/l.
91	I IICIICIIC			

- Trade Effluent Disposal: The treated effluent shall be used for spraying mine pits to the maximum possible extent and excess shall be discharged into local (iv) nalla only after achieving above standards. The project authorities shall take proactive initiatives for use of this excess water for agricultural purposes in the vicinity of mine.
- Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate (V) and maintain the same continuously so as to achieve the quality of treated effluent to the following standards. 100 mg/l.
  - Not to exceed Suspended Solids (1) 100 mg/l. Not to exceed BOD 3 days 27° C. (2)

- Sewage Effluent Disposal: The treated domestic effluent shall be used on land (vi) for gardening / irrigation purpose only.
- Non-Hazardous Solid Wastes: (vii)

Treatment Disposal Type of waste Quantity The waste i.e. Over burden shall be disposed for by means of backfilling or Reclamation of the land.

- (viii) Other conditions: The industry shall monitor effluent quality regularly.
- The applicant shall comply with the provisions of the Water ( Prevention & Control of Pollution ) Cess Act, 1977 ( to be referred as Cess Act ) and Amended Rules, 2003 there under:

water consumption for the following categories is as under:

	consumption for the following categories is as an arrange	Quantity
Sr No	Consumption	120.0 CMD
1	Domestic	6508.0 CMD
2	Mine Discharge	172.0 CMD
3	Spraying, Workshop, dust Suppression	CMD
4	Sand stowing	CMD
5	Other uses like gardening Etc	CIVID

CONDITIONS UNDER AIR ACT: 5.

- The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and (1) operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
  - (A) Standards for Ambient Air Pollutants:

600 ug/Nm<sup>3</sup> (i) Suspended Particulate Matter [SPM] Not to exceed 300 ug/Nm<sup>3</sup> (ii) Respirable Particulate Matter [RSPM] Not to exceed

[Size less than 10 micrometer]

120 ug/Nm<sup>3</sup> Not to exceed (iii) Sulphur Dioxide (SO<sub>2</sub>) 120 ug/Nm<sup>3</sup>. Not to exceed (iv) Oxides of Nitrogen (NOx)

(B) Standards for Emissions of Air Pollutants:

150 mg/Nm<sup>3</sup> Not to exceed TPM (i) Not to exceed -- Kg/Day SO<sub>2</sub> (ii)

(C) Control Equipment:

- Coal handling plant will be provided with Dust Collector and Automatic Water Sprinkler.
- Scientific spraying of water on all working area, dump area, stock piles with the help of appropriate dust suppression system .

Coal shall be properly covered during transportation.

- iv) The applicant shall carry out tree plantation along road side, around dumps or Compulsory afforestation as per proposal approved by Forest Department. The tree plantation programme shall be taken up well in advance of the actual mining activity, so that green belt of sufficient width and height is developed between mining area/road and surrounding environment.
- Black topped metalled roads shall be provided and well maintained to prevent dust formation.

vi) Overloading of dumpers shall be avoided to prevent spillages.

vii) Correct type and quantity of explosive shall be used to avoid excess dust formation and vibration in the surrounding area.

viii) The slope of the over burden shall have slope but not more than 28 degree to the horizontal. The overburden shall be properly covered by vegetation for Stabilization.

ix) Coal transportation shall be done by installing conveyors wherever possible & mechanically covered closed trucks shall be used for transportation.

The applicant shall observe the following fuel pattern:-

Quantity Type of Fuel Sr.No.

The applicant shall erect the chimney(s) of the following specifications:-(III)Height in Mtrs. Chimney attached to Sr.No.

- (IV) The applicant shall provide minimum three ambient air quality monitoring stations within mining area which should be monitored for SPM, RSPM, SO<sub>2</sub>, NOx, HC, CO etc. The Annual Arithmetic Mean of minimum 104 measurements in a year taken twice a week 24 hourly at uniform interval shall conform to the National Ambient Air Quality Standards prescribed under Air (Prevention and Control of Pollution) Act, 1981 and Environment (Protection) Act, 1986. The records of results of continuous monitoring done shall be made available for inspection to the officers of the Board.
- (V) The applicant shall take adequate measures for control of noise levels from its own Sources as follows:

Sr.No.	Location	Permissible Norms [in dB(a)]	Desired minimum thickness of Green Belt
1	Along road	65 (Commercial Area)	20
2	In Colonies	55 (Residential Area)	20
3	Near Opencast Mines	75 (Industrial Area)	10 (*40)
4	Near CHPs	75	30
5	Near Shaft	75	20
6	Near Mine exhaust fan	75	>50

(\* The Open Cast Mine needs to be surrounded by a green belt of sufficient width as per the guidelines of Design Institute Ltd. (A Subsidiary of Coal India Ltd.] if the residential complexes are very close).

### (VI) Other Conditions:

- 1. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- If Coal Washeries are installed, then follow the conditions of the Ministry of Environment &Forests, Government of India's Notification No.Q.15017/13/9 CPW, dated 27th January, 1999 strictly.

#### 6. CONDITIONS UNDER HW (M,H &TM) RULES, 2008:

(i) The applicant shall handle hazardous wastes as specified below:

Sr. No.	Item No. as per Sch-I	Type of Waste	Quantity	Disposal
Indus	stry shall not ger	nerate any hazardo	us waste.	BURNESS BURNESS

#### 7. General conditions:

- (i) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30<sup>th</sup> September every year on available open plot area, no. of trees surviving as on 31<sup>st</sup> March of the year and no. of trees planted by September end.
- (ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- (iii) The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm shall submit MPCB, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30<sup>th</sup> September every year.
- (v) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.

- (vi) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- (vii) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- (viii) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- (ix) The applicant shall maintain good house keeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants. The project authorities shall work out the feasibility of deploying mechanically closed trucks for transportation and submit action plan within 3 months.
- 8. The project authorities shall submit an action plan for using closed coal conveyor belt system in place of truck transportation, wherever the coal transportation distances is less than 3 Kilometers initially, within 3 months.
- 9. The project authorities shall identify critical road sections where the dust generated from coal transportation is likely to affect human population and/or agriculture and take up works of making those roads pucca and clean.
- 10. The project authorities shall install well designed water sprinkling arrangements including fixed and mobile sprayers for dust suppression.
- 11. The project authorities shall give suitable training to field level mine personnel and truck drivers on environmental protection and pollution control.
- 12. The project authorities shall obtain consent for their railway siding operation.
- 13. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 14. The applicant shall comply with the conditions stipulated in Environment Clearance granted by MoEF,Gol vide letter No. J-11015/31/2009-IA.II(M), dt: 22.07.2009.
- 15. Industry shall implement mechanical close type transportation system for coal handling trucks and also introduce closed type conveyer belt transportation of coal from mines.
- 16. The applicant shall submit the operation BG of Rs. 5.0 Lakhs within 15-days drawn in favour of RO, MPCB, Chandrapur, valid upto: 30/07/2017 towards operation and maintenance of Pollution control system so as to achieve the standards prescribed in consent. Bank guarantee will be forfeited if not adhering to the consent conditions
- 17. This consent is issued with the overriding effects to earlier consent issued vide no: BO/JD(APC)/EIC NO: CH-0875-12/R/CC-646, dt: 09/11/2012, valid till: 31/03/2017.

18. Total Capital investment of the Mine is Rs. 15.50/- Crs.

For and On Behalf of the Maharashtra Pollution Control Board,

Joint Director (Air Pollution Control)

To,
M/s. Western Coal Fields Ltd,
Nandgaon Incline,
WCL Chandrapur Area, Po. Nandgaon (Pode),
Tal & Dist. -Chandrapur.

Page 4 of 5

## Copy to:

- 1) Regional Officer, MPCB, Chandrapur, 2) Sub-Regional Officer, MPCB, Chandrapur They are directed to obtain the bank guarantee from the industry as per consent condition no. 16 and submit the performance report along with the monitoring results to the Board office, without fail.
- 3) Chief Accounts Officer, MPCB Mumbai.

Received Consent fee of -

Sr. No.	Amount (Rs.)	DD. No.	Date	Drawn On	
1	2,95,000/-	770212	27/09/2013	UCO Bank	

4) Cess Branch, MPCB.

5) Master file.