MAHARASHTRA POLLUTION CONTROL BOARD

T. I. 0404040=1040	OFFOLION	COMIKOL BO
Tel: 24010437/24020781/24014701	MAHARASHTRA	Kalpataru Point, 2 nd - 4
Fax: 24024068 / 24023516		Opp. Cine Planet Cinen
Website: http://mpcb.gov.in	***	Near Sion Circle, Sion (
E-mail: apae@mpcb.gov.in	1	Mumbai-400 022.

Red/MS.I

Date: 31/07/2014

ith Fl. na,

Consent No: BO/JD(APC)/TB-3/EIC No. PN-21070-14/R/CC-7250

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Q. H. Talbros Ltd., Gat No. 1268 to 1271, Shirwal, Tal- Khandala, Dist – Satara.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to --- 30/11/2014.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Auto Components assemblies with powder coating & painting	4,05,000	Nos/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 4.0 M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 15.0 M3.
- (iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Sr.no	Parameter		Limits
1	pH	Between	5.5 to 9.0
2	BOD 3 days 27 Deg. C	Not to exceed	100 mg/l
3	COD	Not to exceed	250 mg/l
4	Oil & Grease	Not to exceed	10 mg/l
5	TDS	Not to exceed	2100 mg/l.
6	Chlorides	Not to exceed	600 mg/l.
7	Sulphates	Not to exceed	1000 mg/l.
8	Phosphate	Not to exceed	5.0 mg/l.

M/s. Q. H. Talbros Ltd., SRO Satara /I/R/L/87589000

Rage 1 of 6

- (iv) Trade Effluent Disposal: The treated industrial effluent shall be recycled to the maximum extent and remaining shall used on land for gardening. There shall not be any discharge outside the factory premises. Industry should not discharge any effluent in to local nalla.
- Sewage Effluent Treatment: The applicant shall provide comprehensive (v) treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids

Not to exceed

100 mg/i.

BOD 3 days 27o C. (2)

Not to exceed

100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type of Waste	Quantity	Disposal
1	Wooden Board scrap / Boxes scrap	500 kg/D	Sale
2	Burr Scrap	500 Kg/D	Sale

- (viii) Other Conditions: Industry should monitor effluent quality regularly.
- The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic

(ii) Industrial Processing

03 CMD

(iii) Industrial Cooling

06 CMD

(viii) Agriculture

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

A. Control Equipment:

- 1. Fume extraction system of sufficient capacity followed by dust collector, wet scrubber shall be provided to phosphating section & shall be operated regularly.
- 2. The painting activity shall be carried out in closed shed.
- 3. There shall not be any secondary (fugitive) emissions.
- B. Standards for Emissions of Air Pollutants:

(i) SPM/TPM Not to exceed

mg/Nm³ 150

(ii)

SO2

Not to exceed

kg/D 18

C. The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	HSD	0.90	KL/D

M/s. Q. H. Talbros Ltd., SRO Satara /I/R/L/87589000

D. The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	DG Set (250 KVA)	47
2	Phosphating section	11.0
3	Paint booth (new)	1.5 above roof
4	Powder coating oven	1.5 above roof

- E. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- F. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

G. Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

H. Conditions for D.G. Set

- I. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- II. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- III. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- IV. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- V. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- VI. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use

M/s. Q. H. Talbros Ltd., SRO Satara /I/R/L/87589000

Page 3 of 6

- VII. D.G. Set shall be operated only in case of power failure The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set
 - 5. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:
 - (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type of waste	Qty	UOM	Disposal
1	5.1 Waste oil	120	Litr/D	Authorized reprocessor / Recycler
2	5.2 Oil Cotton waste	60	Kg/d	CHWTSDF
3	12.5 Pre treatment sludge	5.0	Kg/d	CHWTSDF
4	21.1 Powder/ Paint sludge	10.0	Kg/d	CHWTSDF
5	34.3 ETP Sludge	5.0	Kg/D	CHWTSDF
6	33.3 Discarded containers	7.0	Nos/D	CHWTSDF

- (ii) Treatment: NIL
- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008.
- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008: and shown & submitted to the Board as & when asked for.
- 6. Industry shall comply with following additional conditions:
 - i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
 - ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.

Page 4 of 6

- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- ix. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 7. The industry shall extend existing bank guarantee of Rs.1.0 Lakh validity upto 31.03.2015 and submit at Regional Office, Pune within 15 days towards operation and maintenance of pollution control system and compliances of consent conditions with the
- 8. The applicant are hereby directed to submit the resolution from company's Board that you have made expansion without obtaining permission from the Board and violated the provisions of Environmental Laws and in future, you will not do such violation within one month period to the Board. If industry authority fails to submit the above said resolution within one month period consent will be treated as cancelled.

Page 5 of 6

- 9. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 10. The Capital investment of the industry is Rs.16.28/- Crs.

For and On Behalf of the Maharashtra Pollution Control Board,

(V. M. Motghare) 303

Joint Director (Air Pollution Control)

To, M/s. Q. H. Talbros Ltd., Gat No. 1268 to 1201m Shirwal, Tal- Khandala, Dist – Satara.

Copy to:

 RO- MPCB Pune/SRO-MPCB Satara- They are directed to ensure the compliance of consent conditions & obtain fresh operational BG of Rs.1,00,000/- from the industry as per the above consent condition.

CAO/Cess Branch/Master File Received Consent fee of –

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	Rs.51,100/-	686577	15.01.2014	SBI Bank