MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 24010437/24014701/24020781

Fax: 24024068/24023516 Website: http://mpcb.gov.in. E-Mail: jdair@mpcb.gov.in



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Rd. No.8, Opp. Sion Circle, Sion (East),

Mumbai-400 022.

RED/LSI

Consent No: BO/JD(APC)/EIC No: NG-12745-15/R/CC-12174 Date: 19/09/2015

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule-5 of the Hazardous Wastes (Management Handling & Transboundry Movement) Rules, 2008.

[To be referred as Water Act, Air Act and HW (MH & TM) Rules respectively].

CONSENT is hereby granted to,

M/s Hindustan Composite Ltd.

Plot No: C-10/1, MIDC, Gadegaon, Tal & Dist: Bhandara.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(MH&TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period up to - 31/03/2017.

2. The Consent is valid for the Manufacturing of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Clutch facings	250000	No/Month
2	Industrial break linings	2	MT/Month
3	Asbestos Mill board/industrial text products	40	MT/ Month
4	Resins (Intermediate process for captive consumption)	62	MT/ Month
5	Non asbestos industrial textile product	40	MT/Month
6	Non asbestos Ceramic Clutch Button	80000	Nos/Month

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 4.5 m³.

(ii) The daily quantity of sewage effluent from the factory shall not exceed 29.0 m³.

(iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

	T		
1	pH	Between	5.5 to 9.0
2	BOD 3 days 27 deg C	Not to exceed	100 mg/l
3	COD	Not to exceed	250 mg/l
4	Suspended solids	Not to exceed	100 mg/l
5	Oil & Grease	Not to exceed	10 mg/l
6	Sulphates	Not to exceed	1000 mg/l.
7	Chlorides	Not to exceed	600 mg/l.
8	TDS	Not to exceed	2100mg/l

Som

SRO Bhandara/I/R/M/30430000

Page 1 of 4

- (iv) Trade Effluent Disposal: The treated effluent shall be reused / recycled in the process completely. There shall not be any discharge outside the factory premises.
 - (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids BOD 3 days 27° C. (2)

Not to exceed Not to exceed

100 mq/l. Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a (vi) soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

' '		9.		
<u>S. No.</u>	Type of waste	Quantity	Treatment	Disposal
1.	Fine Dust from Grinding Mill	1.5 MT/Month	Reus	sed in Process
2.	Boiler Ash	1.4 MT/day	By sale to brid	k manufacturer

(viii) Other conditions: The industry shall monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under: The daily water consumption for the following categories is as under:

(i) Domestic	35.0 CMD
(ii) Industrial Processing	7.0 CMD
(iii) Industrial Cooling	27.0 CMD
(iv) Agriculture/Gardening	0.0 CMD
(v) Other	0.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

CONDITIONS UNDER AIR ACT: 5.

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

A) Control Equipment:

- Fume extraction followed by dust collection system provided to wet mixing , dry mixing section and any other sources of TPM/SPM shall be operated & maintained properly & continuously.
- 2. There shall not be any secondary (fugitive) emissions.

B) Standards for Emissions of Air Pollutants:

ioi Ennasions of All I offula	iilo.	
(i) SPM/TPM	Not to exceed	150 mg/Nm ³
(ii)SO2	Not to exceed	97 Kg/D
(iii) Plain asbestos Material	Not to exceed	0.5 Fibre/CC
(iv) Total dust	Not to exceed	2.0 mg/Nm ³

C) Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

SRO Bhandara/I/R/M/30430000

- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(ii) The applicant shall observe the following fuel pattern:-

	with origin opposite title	ionowing fuel pat
Sr.No.	Type of Fuel	Quantity
1.	Coal	9.0 MT/day
2.	HSD	15 Lit/hr

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr.No.	Chimney attached to	Height in Mtrs.
1	Boiler	30
2	D G Set 110 KVA	2*

(* Above the roof top of the building in which it is installed)

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted /displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) Other Conditions:
 - 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MH &TM) RULES, 2008:

(i)The applicant shall handle hazardous waste as specified below:-

Sr. I	Nc HW Ca	Type Of Waste	Quantity	UOM	Disposal
1	15.1	Asbestos-containing residues	30.00	MT /Annum	
2	15.2	Discarded asbestos	5.00	MT /Annum	CHWTSDF
3	15.3	Dust particulates from exhaust gas treatment	30.00	MT /Annum	Butibori, Nagpur
4	33.3	Discarded containers / barrels / liners	15000	Nos/Annum	

(ii) The authorization is here by granted to operate a facility for collection, storage, transport & disposal of hazardous waste.

- 7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 8. General conditions:
- (i) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- (iii) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

Page 3 of 4

- The firm shall submit MPCB, the Environmental Statement Report for the financial year (iv) ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September
- The applicant shall install a separate meter showing the consumption of energy for (V) operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- Separate drainage system shall be provided for collection of trade and sewage (vi) effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- The applicant shall provide facility for collection of environmental samples and samples (vii) of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- The industry shall ensure that fugitive emissions from the activity are controlled so as to (viii) maintain clean and safe environment in and around the factory premises.
- The applicant shall maintain good house keeping and take adequate measures for (ix) control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- This Board reserves the right to amend or add any conditions in this consent and the 9. same shall be binding on the Applicant.
- Industry shall provide Sewage Treatment Plant (STP) on or before 31/01/2016 and 10. shall submit BG of Rs. 5.0 Lakhs towards compliance of the same.
- The applicant shall submit fresh bank guarantee of Rs. 5.0 Lakh drawn in favour of 11. Regional Officer, MPCB Nagpur within 15-days valid upto: 31/07/2017 towards operation and maintenance of pollution control system so as to achieve the consented standards.
- Total Capital investment of industry is Rs. 18.54/- Crore. 12.

For and On Behalf of the Maharashtra Pollution Control Board,

(V.M. Motghare)

Joint Director (Air Pollution Control)

To,

M/s Hindustan Composite Ltd,

Plot No: C-10/1, MIDC, Gadegaon,

Tal & Dist: Bhandara.

Copy to:

- 1) Regional Officer, MPCB, Nagpur, 2) Sub-Regional Officer, MPCB, Bhandara.
 - They are directed to forefit existing BG of Rs. 2.0 Lakhs & obtain fresh BG's of as per condition no: 10 & 11 & submit the performance report along with the monitoring results within one month period.
- 3) Chief Accounts Officer, MPCB, Mumbai

Received Consent fee of -

			D O
Amount (Rs.)	DD. No.	Date Drawn	Drawn On
65.100/-	371078	22/04/2015	Syndicate Bank
	Amount (Rs.) 65,100/-	27/272	AITOUTT 1007