MAHARASHTRA POLLUTION CONTROL BOARD

4010437/4020781 Phone :

/4037124/4035273

24044532/4024068 /4023516 Fax 8

Email : enquiry@mpcb.gov.in Visit At: http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E),

Mumbai - 400 022

Consent order No: - BO/CAC-Cell/EIC No:-KP-17074-15/CAC/847 Date- 19/01/20/6

M/s. Kirloskar Oil Engines Ltd. ,

Plot No. D-1 Five Star MIDC Kagal-Hatkanangle,

A/p.- Talandage, Dist.-Kolhapur-416216

Subject: Renewal of consent to operate with increased CI in RED category.

Ref

- : 1. Earlier 1st consent to operate with amalgamation of existing consent granted vide no. Format 1.0/BO/CAC-Cell/EIC No. KP-13585-13/18th CAC/CC/CAC-1723 dtd. 24.02.2014
 - 2. Your application is approved in CAC meeting held on 09.12.2015.

Your application :- CR1503000065

Dated: 13.01.2015

For: Renewal of Consent to operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II ,III & IV annexed to this order:

- 1. The consent is granted for a period from 28,02,2015 to 28.02,2020.
- 2. The actual capital investment of the industry is Rs.713.57Crs. (Existing CI-Rs. 622.19 Cr + increased CI- Rs. 91.38 Cr as per C.A. Certificate_submitted by industry)

3. The Consent is valid for the manufacture of -

| Sr. No. | Product / By-Product Name | Maximum Quantity |
|------------|---------------------------|------------------|
| 1 | I.C. Engines | 10,000 Nos./M |
| 2 | Generating sets | 1,625 Nos./M |
| 3 | Pumpsets | 8,000 Nos./M |

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

| Sr. no. | Description | Permitted quantity of discharge (CMD) | Standards to be achieved | Disposal |
|------------|-------------------|---|-----------------------------|-----------------------|
| 1. | Trade effluent | 115 | As per Schedule -I | On land for gardening |
| 2. | Domestic effluent | 140 | As per Schedule -I | On land for gardening |

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

| Sr. | Description of stack / source | Number of Stack | Standards to be achieved |
|-----|----------------------------------|-----------------|--------------------------|
| 1 | 5625KVA HFO Stand by Genset | 1 | As per Schedule -II |
| 2 | ME Paint Booth | 5 10 | As per Schedule -II |

M/s. Kirloskar Oil Engines Ltd., SRO Kolhapur/I/R/L/43438000

Page 1 of 11

| Sr. | Description of stack / source | Number of Stack | Standards to be achieved |
|-----|--|-----------------|-----------------------------|
| 3 | ME Paint Booth | 2 | As per Schedule -II |
| 4 | SE Paint Booth | 1 | As per Schedule -II |
| 5 | Pump Set Paint Booth | 1 | As per Schedule -II |
| 6 | Pump Set Paint Booth | 4 | As per Schedule -II |
| 7 | Medium Engine Test Bed | 3 | As per Schedule -II |
| 8 | SE Test Bed | 1 | As per Schedule -II |
| 9 | Pump Set Test Bed | 1 | As per Schedule -II |
| 10 | Gen Set Test Bed | 2 | As per Schedule -II |
| 11 | Stand by Gen Set 600 KVA | 5 | As per Schedule -II |
| 12 | Stand by Gen set 125 KVA | 1 | As per Schedule -II |
| 13 | Fire Hydrant Pump driving Engine | 1 | As per Schedule -II |
| 14 | Thermic Fluid Heater | 1 | As per Schedule -II |
| 15 | Pretreatment area at powder coating section for canopy | 2 | As per Schedule -II |
| 16 | Powder coating section for canopy | 1 | As per Schedule -II |
| 17 | SL-90 Engine Paint Booth | 1 0 | As per Schedule -II |
| 18 | SL-90 Engine Paint Booth | 1 (0 | As per Schedule -II |
| 19 | SL-90 Engine Paint Booth | 1_ \ | As per Schedule -II |
| 20 | DV Engine Paint Booth | 1 | As per Schedule -II |
| 21 | DV Engine Paint Booth | (1) | As per Schedule -II |
| 22 | DV Engine Paint Booth | | As per Schedule -II |
| 23 | DV Engine Test Beds | 3 | As per Schedule -II |
| 24 | 6R Engine Test Beds | 2/1/2 4 | As per Schedule -II |
| 25 | HA6 Engine Test Beds | 3 | As per Schedule -II |
| 26 | SL-90 Engine Test Beds | 2 | As per Schedule -II |
| 27 | Gen Set Test Bed | 3 | As per Schedule -II |
| 28 | Stand by Genset | 3 | As per Schedule -II |
| 29 | Kitchen Boiler | 1 | As per Schedule -II |

6. Conditions about Non Hazardous Wastes:

| SR. NO. | Product Description | Qty. & UOM | Treatment | Disposal Method |
|------------|--|------------------|-----------|---------------------------|
| 1 | Metal Scrap | 430 MT/M | N.A. | Sale to authorized vendor |
| 2 | Garbage | 87 MT/M | N.A. | Sale to authorized vendor |
| 3 | Wooden Scrap | 78.13 MT/M | N.A. | Sale to authorized vendor |
| 4 | Rubber Plastics | 117 MT/M | N.A. | Sale to authorized vendor |
| 5 | Waste corrugated boxes | 50 MT/M | N.A. | Sale to authorized vendor |
| 6 | Cotton waste | 1.5 MT/M | N.A. | Sale to authorized vendor |
| 7 | Empty Paint Barrels/Containers/Empty aerosol Bottles | 44,000 Nos./M | N.A. | Sale to authorized vendor |

M/s. Kirloskar Oil Engines Ltd., SRO Kolhapur/I/R/L/43438000

Page 2 of 11

| SR. NO. | Product Description | Qty. & UOM | Treatment | Disposal Method |
|------------|-------------------------------|---------------|-----------|---------------------------|
| 8 | Grinding Dust | 21 MT/M | NA | Sale to authorized vendor |
| 9 | Waste Welding Glass | 200 Nos./M | NA | Sale to authorized vendor |
| 10 | Biosludge from ETP, Biogas | 500 Kg/M | NA | Sale to authorized vendor |

7. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and

| disposal of h | azardous | waste: |
|---------------|----------|--------|
|---------------|----------|--------|

| SR. NO. | Type of waste | Category | Total Qty. | UoM | Disposal |
|------------|--|-----------|------------|--------|-----------------------------------|
| 1 | USED & WASTE OIL, LUBE OIL SLUDGE, HFO CENTRIFUGAL SLUDGE | 5.1 & 5.2 | 7.0 | KL/Day | SALE TO AUTHO. REPROCESSOR |
| 2 | OIL SOAKED COTTON | 5.2 | 2.0 | MT/M | CHWTSDF |
| 3 | PAINT SLUDGE | 21.1 | 7.7 | MT/M | CHWTSDF |
| 4 | ETP SLUDGE | 34.4 | 46 | MT/M | CHWTSDF |
| 5 | CONTAMINATED SOLVENT | 20.1 | 0.2 | MT/M | CHWTSDF |
| 6 | LEAD ACID BATTERIES | *** | 800 | Kg/M | CPCB Recycler |
| 7 | PHOSPHATE SLUDGE | 12.5 | 1600 | Kg/M | CHWTSDF |
| 8 | DISCARDED LINERS CONTAMINATED WITH POWDER e.g. HANGERS | 33.3 | 1000 | Kg/M | CHWTSDF |
| 9 | WASTE EPOXY POWDER | 21.1 | 2030 | Kg/M | CHWTSDF |
| 10 | DISCARDED CONTAINERS.BARRELS CONTAMINATED WITH OILS & CHEMICALS | 33.3 | 1550 | Nos./M | Send back to Manufacturer. |
| 11 | CONTAMINATED AERSOL CANS | 33.3 | 900 | Nos./M | SALE TO AUTHO, REPROCESSOR |
| 12 | WASTE ROCKWOOL/ WASTE GLASS TISSUE PAPER | 21.1 | 1030 | Kg/M | CHWTSDF |
| 13 | WASTE SOFTNER RESIN | *** | 700 | Kg/Y | CHWTSDF |
| 14 | E-WASTE | *** | 1500 | Kg/M | E-WASTE PROCESSING FACILITY |
| 15 | GRINDING WHEELS | *** | 2.0 | MT/Yr. | CHWTSDF |
| 16 | FILTER PAPER, OIL FILTER | - " | 600 | Kg/M | CHWTSDF |
| 17 | USED TUBELIGHTS/BULBS | 7-1 | 210 | Kg/M | CHWTSDF |

M/s. Kirloskar Oil Engines Ltd., SRO Kolhapur/I/R/L/43438000

Page 3 of 11

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.

For and on behalf of the Maharashtga Pollution Control Board

> (Dr. P. Anbalagan, IAS) Member Secretary

Received Consent fee of -

| Sr. No. | Amount (Rs.) | DD. No. | Date | Drawn On |
|------------|-----------------|---------|------------|---------------|
| 1 | Rs. 28,54,306/- | 637106 | 06.01.2015 | HDFC Bank Ltd |
| 2 | Rs. 1,25,000/- | 637105 | 06.01.2015 | HDFC Bank Ltd |
| 3 | Rs. 100/- | 637107 | 06.01.2015 | HDFC Bank Ltd |
| 4 | Rs. 42,81,459/- | 364425 | 06.01.2016 | HDFC Bank Ltd |

Copy to:

- Regional Officer Kolhapur and Sub-Regional Officer-Kolhapur, MPCB, They
 are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updation purposes.

Schedule-I

Terms & conditions for compliance of Water Pollution Control:

 Al As per your application, you have provided the Effluent Treatment Plant (ETP) for primary treatment of trade effluent and further treated in Sewage Treatment Plant (STP) of design capacity 360 CMD.

B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time,

whichever is stringent.

| Sr No. | Parameters | Standards prescribed by Board (If any) | |
|--------|-----------------------------|---|--|
| | I. Compulsory Parameters | Limiting Concentration in mg/l, except for pH | |
| 01 | pH | 5.5-9.0 | |
| 02 | Oil & Grease | 10 | |
| 03 | BOD (3 days 27oC) | - 100 | |
| 04 | Total Dissolved Solids | 2100 | |
| 05 | Suspended Solids | 100 | |
| 06 | COD | 250 | |
| 07 | Chloride | 600 | |
| 08 | Sulphates | 1000 | |

- C] The treated effluent shall be used on land for gardening on 28.42 acres after confirming the above standards. In no case treated effluent shall be discharged directly/indirectly on outside the factory premises.
- A] As per your consent application, you have provided the sewage treatment system with the design capacity of 360 CMD.
 - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

| (1) | Suspended Solids. | Not to exceed | 50 | mg/l. |
|-----|-------------------|---------------|-----|-------|
| (2) | BOD 3 days 27oC. | Not to exceed | 30 | mg/l. |
| (3) | COD | Not to exceed | 100 | mg/l. |

- C] The treated effluent shall be used on land for gardening on 28.42 acres after confirming the above standards. In no case treated effluent shall be discharged directly/indirectly on outside the factory premises.
- D] In case the treatment system is combined for trade effluent and sewage then the standards and disposal path prescribed at sr. no.1 B & C of schedule I shall be applicable.
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition thereto.

3438000

Page 5 of 11

- 4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
- 5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

| Sr. no. | Purpose for water consumed | Water consumption quantity (CMD) |
|------------|--|----------------------------------|
| 1. | Industrial Cooling, spraying in mine pits or boiler feed | 85 |
| 2. | Domestic purpose | 155 |
| 3. | Processing whereby water gets polluted & pollutants are easily biodegradable | 125 |
| 4. | Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic | Nil |

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also erected following stack (s) and to observe the following fuel pattern-

| Sr. No. | llowing fuel pa Stack Attached to | APC System | Heigh t in Mtrs. | Type of fuel | Quantity & UOM % | S% | SO2 Kg/da y |
|------------|---|--|------------------------|--------------------|-----------------------------|------|-------------------|
| | 5625KVA | Exhaust | 52 | HFO | 10 KL./day | 4 | 3200 |
| | HFO Stand by Genset | Silencer, diffuser provided. | 40.00 | HSD | 24 KL/day | 1 | 480 |
| 2 | ME Paint Booth | Water Curtains provided | 11 | HSD | 100 lit./day | 1 | 2 |
| 3 | ME Paint Booth | Water Curtains provided | 11 | N.A. | N.A. | N.A. | N.A. |
| 4 | SE Paint Booth | Water Curtains provided | 11 | N.A. | N.A. | N.A. | N.A. |
| 5 | Pump Set Paint Booth | mp Set Water Curtains | | HSD | 100 lit./day. | 1 | 2 |
| 6 | Pump Set Paint Booth | p Set Water Curtains | | N.A. | N.A. | N.A. | N.A. |
| 7 | Medium Engine Test Bed | Exhaust Silencer, diffuser provided. | 33 | HSD | 800 lit./day | 1 | 16 |
| 8 | SE Test Bed | Exhaust Silencer, diffuser provided. | 33 | HSD | 400 lit/day | 1 | 8 |
| 9 | Pump Set Test Bed | Exhaust Silencer, diffuser provided. | 33 | HSD | 300 lit/day | 1 | 6 |
| 10 | Gen Set Test Bed | Exhaust Silencer, diffuser provided. | 33 | HSD | 1000 lit/day | 1 | 20 |
| 11 | Stand by Gen Set 600 KVA Enclosure provided | | 13 | HSD | 10 KL/day | 1 | 200 |
| 12 | Stand by Gen set 250 KVA | Acoustic Enclosure provided | 13 | HSD | 300 lit/day | 1 | 6 |
| 13 | Fire Hydrant Pump driving Engine | | 13 | HSD | 300 lit/day | 1 | 6 |
| 14 | Thermic Fluid Heater | **** | 11 | LPG/ PNG | 30,000 Kg/day /725SCM | N.A. | N.A. |
| 15 | Pretreatment area at powder coating section for canopy | tore | 15 | N.A. | N.A. | N.A. | N.A. |
| 16 | Powder coating section for canopy | **** | 15 | N.A. | N.A. | N.A. | N.A. |

M/s. Kirloskar Oil Engines Ltd., SRO Kolhapur/I/R/L/43438000

Page 7 of 11

| Sr. No. | Stack Attached to | APC System | Heigh t in Mtrs. | Type of fuel | Quantity & UOM % | S% | SO2 Kg/da y |
|------------|-----------------------------|--|------------------------|--------------------|---------------------|------|-------------------|
| 17 | SL-90 Engine Paint Booth | Water Curtains provided | 11 | HSD | 100 lit./day | 1 | 2 |
| 18 | SL-90 Engine Paint Booth | Water Curtains provided | 11 | N.A. | N.A. | N.A. | N.A. |
| 19 | SL-90 Engine Paint Booth | Water Curtains provided | 11 | N.A. | N.A. | N.A. | N.A. |
| 20 | DV Engine Paint Booth | Water Curtains 10 N.A. N.A. | | N.A. | N.A. | N.A. | |
| 21 | DV Engine Paint Booth | Water Curtains provided | 10 | N.A. | N.A. | N.A. | N.A. |
| 22 | DV Engine Paint Booth | Water Curtains provided | 10 | N.A. | N.A. | N.A. | N.A. |
| 23 | DV Engine Test Beds | Exhaust Silencer, diffuser provided. | 14 | HSD | 0 | 09/ | 60 |
| 24 | 6R Engine Test Beds | Exhaust Silencer, diffuser provided. | 14 | HSD | 3100 | 0 | |
| 25 | HA6 Engine Test Beds | Exhaust Silencer, diffuser provided. | 14 | HSD | Lit./day | | 62 |
| 26 | SL-90 Engine Test Beds | Exhaust Silencer, diffuser provided. | 14 | HSD | | | |
| 27 | Gen Set Test Bed | Exhaust Silencer, diffuser provided. | 134 | HSD | 6 KL/day | 1 | 120 |
| 28 | Stand by Genset | 00 | 11 | HSD | 6KL/day | 01 | 120 |
| 29 | Kitchen Boiler | 830 | 6 | LPG | 100 Kg/day | N.A. | N.A. |

- The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines. (Concern section shall mention specific control equipments)
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

| Particulate matter | Not to exceed | 150 mg/Nm ³ . | |
|--------------------|---------------|--------------------------|--|
|--------------------|---------------|--------------------------|--|

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacementalteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

my

Page 8 of 11

Schedule-III Details of Bank Guarantees

| Sr. No. | Consent (C to E/O/R) | Amt of BG Imposed | Submissi on Period | Purpose of BG | Complian ce Period | Validity Date |
|------------|----------------------------|-----------------------------------|--------------------------|--|-----------------------|------------------|
| 1 | CtoO | Rs. 5 lakh (to be extended) | 15 days | Towards operation and maintenance of pollution control system | 28.02.2020 | 30.06.2020 |

Schedule-IV

General Conditions:

- The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 5) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent (in case of Renewal of consent).
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set

 Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.

- d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f) D.G. Set shall be operated only in case of power failure.
- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEF dated 17.05,2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a statement on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end, with the Environment Statement.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit quarterly statement in respect of industries' obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can be downloaded from MPCB official site).
- 26) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 27) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

-0000— Muy /43438000