MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

E-mail: ast@mpcb.gov.in

Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

RED/LSI

Consent order No:-Format 1.0/AST/RO-KN/EIC No. KN-6739-15/R/CC-2660

Date-23/02/2016

To.

M/s. Metropolitan Exim Chem Ltd., Plot No. B-CFC, MIDC Phase-II, Dombivali, Dist. Thane.

Subject: Renewal of Consent to Operate in Red Category.

Ref : 1. Consent to operate is granted vide No. BO/AST/RO-KN/EIC-No. KN-6434-13/R/Amnd/CC-2923 dtd. 06.04.2013

2. Minutes of CC meeting held on 03.02.2016

Your application: CR15006000287

Dated: 17.06.2015

For Renewal of Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- 1. The consent is granted for a period from 28.02.2015 to 28.02.2020
- 2. The total capital investment of the industry is Rs. 42.37 Cr. (Existing Rs. 27.77 Cr + Increased Rs. 14.6 Cr) As per C. A Certificate submitted by industry.

3. The Consent is valid for the manufacturing of -

Sr. No.	Product Name	Maximum Quantity in MT/A
1	K-ACID	5
2	2- Acetyl Amino-6- Amino Phenol -4- Sul. Acid	50
3	Para Phenylene Diamine Di Sulphonic Acid	40
4.	3(Phenyl Sulphonyl) Benzene sulphonic acid	50
5	O-NAPSA	40
6	2-Acetyl Aminophenol	5
6810	4- Chloro-2-AminoPhenol 5 Sulphonic acid	10
8	4-Chloro 5-Nitro 2- Amino Phenol	10
9	6-NAPSA	10
10	Formazon Blue	30
11	M-Sulphophenyl Gamma Acid	10
12	5-Nitro 2- Amino Phenol	70
13	HW Amine	5
14	5 AMINO 6 METHYL BENZIMIDAZOLONE	80
15	Anthroniloyl Anthranilic Acid	5
16	Sodium Trichloro Benzene Sulfonate (STB)	5
17	DIAZO ESTER	8
18	DAMAB	10
19	Dicumene	95

Page 1 of 10

M/s. Metropolitan Exim Chem Ltd., SRO Kalyan-1/1/R/L/75068000

20	D- 101(Diazo phosphate)	
21	D- 121(Diazo Chloride)	2
22	2,5-Dichloro p-phenylene Diamine	1
23	N- Ethyl Carbazole	15
24	Para Amino N Methyl Acetanilide	10
25	2 N- Carbethoxy Amino 5- Naphthol 7- Sulphonic	5
	acid Amino 5- Naphthol 7- Sulphonic	10
26	4-chloro Anthranilic acid	
27	5-chloro 8- Hydroxy Quiniline	5
28	2,5- Dimethoxy aniline 4-sulpho phenylamide	100
29	3m6b	5
30	Thio 3m6b	5
31	4-(2CHLOROETHYL SULFONYL)BUTRIC ACID	5
32	2-CHLORO 4-(2CHLOROETHYL	20
	SULFONYL)BUTRIC ACID	10
33	MR3	01
34	BHE	(15
35	2,3 DIBROMOPROPYL CHLORIDE	2
36	3 BROMO PROPYLENE AMIN 4 SULFO	V 5
	ANILINE	5
37	3 AMINO 4(4 AMINO 2 SULFO PHENYL)AZO 5	10
	HIDROXY NAPIHLENE	10
38	4,4 DIAMINO DIAMINO DI PHENYL AMIN	2
0.0	SULPHATE	-
39	ANILINE METHYL OMEGA CARBOXY ACID	5
40	PARA CRISEDENE SULFO METHYL AMIDE	5
41	Capsamide	5
42	D-60	0.150
43	BY PRODUCT	0.130
44	SPENT SULPHURIC ACID	3000
45	ZINC CHLORIDE	100
	UNHYDROUS SOD. SULFATE FOR CAPTIVE	06

(Total Production quantity of finished products shall not exceed 786 MT/A)

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. no.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
	Trade effluent	200	As per Schedule -I	CEMP
2.	Domestic effluent	15		CETP
	une under Air (De Cr	15	As per Schedule -I	Septic Tank

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr. no.	Description of stack / source	Number of Stack	Standards to be achieved
1.	Boiler 4 Nos.	1	As per Schedule -II
2.	Incinerator		As per Schedule -II
3.	Spray Dryer	1	
4.	SO2 Scrubbers 4 Nos.	1	As per Schedule -II
5.	NOx Scrubber		As per Schedule -II
3.	NH3 Scrubber	1	As per Schedule -II
7.		1	As per Schedule -II
	DG Set 250 KVA 2 Nos	2	As per Schedule -II

6. Conditions about Non Hazardous Wastes:

Sr. No.	Type Of Waste	Quantity	A CONTRACTOR OF THE PARTY OF TH	Treatment	Disposal
1	Coal Ash	3.6	MT/D		Sale Brick
ditt	one under H				manufacturer

7. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr		Category	Quantity	UOM	Treatment	Disposal	
1	Waste Oil/ Used oil	5.1	17	KG/M		Dispositi	
2	Wastes and Residues containing oil	5.2	50	KG/M		CHWTSDF/ Incineration	
3	Process waste sludge	26.1	2000	KG/M		Oyon	
4	Chemical Sludge from waste water treatment	34.3	500	KG/M	1/9:	CHWTSDF	
5	Sludge from treatment of waste water arising out of cleaning/dispo sal of barrels/ containers	33.2	5	KG/M	Miles	CHWTSDF	
	Ash from incineration of Hazardous waste	36.2	500	KG/M			

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.
- 10. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.
- 11. Industry shall comply with the EIA Notification, dated 14.09.2006 and amendments thereto.
- 12. Industry shall submit Board Resolution from company Board, towards carrying extra production without obtaining consent to establish from the Board thus violated the provisions of Environmental Laws and in future, they will not do such violations.
- $13.\ This\ consent$ is issued pursuant to the decision of the Consent Committee held on 03.02.2016

For and on behalf of the Maharashtra Pollution Control Board

> Dr. P Anbalagan, IAS Member Secretary

Received Consent fee of-

	.) DD. No.	Amount(Rs.)	Sr. No.
Drawn On	098054	1,62,600/-	1
15 Canara Ba		50,000/-	2
15 Axis Bank	029361		3
	493594		
i	493594 Rs. 62.500/- is con	2,00,000/- ining fees of Rs.	

Remaining fees of Rs. 62,500/- is considered for renewal of this consent.

Copy to:

- 1. Regional Officer -Kalyan and Sub-Regional Officer-Kalyan-I, MPCB, They are directed to ensure the compliance of the consent conditions. Maharashtra Pollution Control Boat
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updating purposes.

Schedule-I

Terms & conditions for compliance of Water Pollution Control:

- 1) A] As per your application, you have provided Effluent Treatment Plant (ETP) with the design capacity of 250 CMD comprising Primary, Secondary and Tertiary treatment.
 - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr No.	Parameters	Standards prescribed by Board
	I. Compulsory Parameters	Limiting Concentration in mg/l, except for pH
01	pH	5.5 to 8.5
02	Oil & Grease	
03	BOD (3 days 27oC)	10.0
04	Suspended Solids	100
05	COD	100
06	Chloride (as Cl)	250
07	Sulphate as (SO4)	600
08	Total Dissolved solids	1000
09	Phenolic Comp.	2100
10	Chromium Cr6+	7/1
11	Sulphides as S	0.10
12	Bio assay test	2
	Dio assay test	90% survival of fish after 96 hours in 100% effluent

- C) The treated effluent shall be recycled to the maximum extent and remaining shall be sent to CETP by providing common outlet to MIDC drainage line.
- 2) A] As per your consent application, you have provided soak pit as a treatment for sewage.
 - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent. (1) Suspended Solids. Not to exceed

100 mg/l.

(2) BOD 3 days 27oC.

Not to exceed

100 mg/1.

- C] The treated sewage shall be used on land for gardening/plantation only in the factory
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition
- 4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

M/s. Metropolitan Exim Chem Ltd., SRO Kalyan-1/1/R/L/75068000

Page 5 of 10

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

	Purpose for water consumed	Water consumption
1.	Industrial Cooling, spraying in mine pits or boiler feed	quantity (CMD) 60
2.	Domestic purpose	
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	20 210
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	NIL
5.	For gardening	1
		20

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.

Jaharashtra Pollution

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also proposed to erect following stack (s) and to observe the following fuel pattern-

Sr. No.	Total To	The state of the s	Height in Mtrs.	Type of Fuel	Quantity & UoM	S %	SO_2
2.	Boiler-II	Dust	Common	Coal	5.2 MT/D	0.5	Kg/Day 52
3.	Boiler-III	with Wet	stack 30				32
4.	Boiler-IV	scrubber	30	FO	1 MT/D	4.5	90
5.	Incinerator		30	LDO	800 Lit/D	3.0	
6.	Spray Dryer		30	FO	0.2 MT/D	1.8	28.8
7.	Plant-I	SO2 scrubber				0	18
8.	Plant-I	SO2 scrubber			180		****
9.	Plant -II	SO2 scrubber	30	36	10)	***	****
10	Plant-II	SO2 scrubber		2000	7	****	****
1	Plant-I	NOx scrubber	30	0	****	****	
2	Plant-I	NH3 scrubber	30				***
3	DG Set 250 KVA 2 Nos	Stack	10	HSD	75 Lit/D		

* Above the roof

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / **Environmental Clearance**

3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	150 ma/N-2
NOx	Not to exceed	150 mg/Nm3
S02	Not to exceed	50 ppm 50 ppm
NH3	Not to exceed	
H2S	Not to exceed	35 ppm 10 ppm

4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution

5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

Schedule-III Details of Bank Guarantees

Bank Guarantee History: Fresh and Existing BG's

Sr. No.	Consent (C to E/O/R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
	C to R	10 Lakh	15 days	Towards O & M of Pollution Control Systems.	28.02.2020	30.06.2020
2	Ctor	2 Lakh	15days	Towards submission of the Board Resolution of the Company Board	29.02.2015	One year
	1000			Company Board	2	0
				My	800	
				1/	0,	
				can)		
				200		
				10/4		
			1	100		
			60			
		13	60			
		.25	,			
		2/0				
	1	10.				
	113	10.				
	Ma	10.				
	Ma	10				
	Mo	10				

Schedule-IV

General Conditions:

- The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- 3) Industry should monitor effluent quality, stack emissions and ambient air quality monthly.
- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.
- 5) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW (MH&TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall obtain Consent to Operate from Maharashtra Pollution Control Board before actual commencement of the Activity.
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (www.mpcb.gov.in).
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

Page 9 of 10

- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall
- 17) Conditions for D.G. Set
 - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
 - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
 - D.G. Set shall be operated only in case of power failure.
 - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
 - h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 26) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 27) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

----0000---

Page 10 of 10