MAHARASHATRA POLLUTION CONTROL BOARD

Fax

/4037124/4035273

Email

24044532/4024068 /4023516

enquiry@mpcb.gov.in

Visit At :

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Mumbai - 400 022

Red/L.S.I

Aug. Date: 04 /Jul/2011

Consent No: BO/PAMS/O/EIC NO.PN-10115-11/CC- 11>

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Cipla Ltd.

Plot No. D-27, MIDC Kurkumbh

Tal- Daund, Dist- Pune, 413 802

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to:. 30.11.2012

2. The Consent is valid for the manufacture of -

or, No.	Product Name	Maximum Quantity	UOM
1	Antiretroviral	Qualitity	
2	Anti inflammatory	×	
3	Anti-Diabetic	100	
	Anti Bacterials	160	MT/YEAR
	Antipsychotic		TO A TEMP
4	Anti-hypertensive		

Note: The industry has obtained Environmental Clearance for total manufacturing capacity of production 320 MT/A, however as per the application from the industry, consent to 1st operate is issued for half of its production capacity i.e. 160 MT/A

CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 143.00M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 35.00M3.

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1 рН	Between	5.5 to 9.0

2	Oil & Grease	The second	
3	Suspended Solids	Not to exceed	10 0
4	BOD (3 d	Not to exceed	10 mg/
	BOD (3 days at 27° c)	Not to exceed	100 mg/l
5	COD	Not to exceed	30 mg/
6	TDS	Not to exceed	250 mg/
7	Chloride	Not to exceed	2100 mg/l
8	Sulphate	Not to exceed	600 mg/l
	Effluent Disposal, m	Not to exceed	1000 mg/i

- (iv) Trade Effluent Disposal: The less concentrated effluent after biological treatment followed by Reverse Osmosis shall be recycled for utility and strong stream effluent will be treated in Multiple Effect Evaporator (MEE) and condensate 18 CMD generated from MEE mixed with less concentrated effluent for further treatment and concentrate 2 CMD will be send to other unit of M/s Cipla Dtd at plot D-7, Kurkumbh, Pune.
- (v) Sewage Effluent Treatment and disposal: The overflow of the septic tank will be mixed along with trade effluent for further treatment as the industry is having biological treatment plant for treatment of trade effluent and the septic tank will be cleaned periodically and to meets the standards as mentioned above at (iii).
- (vi) Non-Hazardous Solid Wastes:

Plastic scrap, Glass scrap,	Qty UOM	Treatment Disposal
rerrous scrap, wooden	120.00 MWYr	Sale to authorised deale
scrap & Metal scrap	1611	222

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and

The daily water consumption for the following categories is as under:

(ii) Water gets Polluted & 45.00 CMD

Pollutants are Biodegradable ...

(iii) Water gets Polluted, Pollutants 130.00 CMD are not Biodegradable & Toxic ...

(iv) Industrial Cooling, spraying 20.00 CMD

in mine pits or boiler feed (iv) Agriculture and gardening etc. ... 70.00CMD 35.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the

5. CONDITIONS UNDER AIR ACT:-

The applicant shall install a comprehensive control system consisting (i) of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:-

- Air pollution control equipment of adequate capacity shall be provided to limit the emissions. 2.
- Dust collector of adequate capacity shall be provided to all source of TPM/SPM i.e. Bulk drugs and air ventilation
- Wet scrubber shall be provided to absorb gaseous emissions 3. from the process 4.
- Standards for Incinerator:
 - a) Incinerator facility at Cipla Plot No. D-7, MIDC, Kurkumbh, shall be used.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day, time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- D.G. Set shall be operated only in case of power failure
- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

Standards for Stack Emissions:

The applicant shall observe the following fuel pattern:-(i)

Sr. No.	Type Of Fuel	Quantity	LOM
	Furnace Oil	4.50	KL/Day
-	Diesel	1.00	KL/Day

The applicant shall erect the chimney(s) of the following (ii)

Sr. No.	Chimney Attached To Boiler	
1	Boiler	Height in Mtrs.

4	DG set-750 KVA	7.50	
3	DG set-1250 KVA	7.50	
	1200 KVA	7.50	

- The applicant shall provide ports in the chimney/(s) and facilities such as (iii) ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate
- The industry shall take adequate measures for control of noise levels from its (iv) own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality
- 3) Standards for emission of VOC Pollutants

Sr. No.	Petrochemical Process Compounds	Maximum emission limit
01	MA, PA, Phenol	(mg/Nm3), dry basis
02	Ethyl benezene (EB), Styrene, Toluene, Xylene, Aromatics, EG, PG	20
03	Non-methane HC (Paraffin), Acetone, olefins	150

- 4) Industry shall made provision of Continuous Emission Monitoring System
- 8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	The Industry shall handle ha Type Of Waste 5.1 Used /spent oil	quantit	y UOM	Disposal
2	20.2 Spent solvents	200.00	Ltrs/M	Sold out to author
3	**************************************	3500.00	Ltrs/M	Sold out to author
4	The Catalyst / short carbon	125.00	Kg/M	processor/vendor
		1500.00	Kg/M	Recycled / Incineration
5	and off-specification drugs/medicine	0.000-808-0-05	178/191	Incineration
	28.5 Spent organic solvents / mother liquor	375.00	M³/M	Francosti
6	33.3 Discarded containers / barrels /			Evaporation Incineration
	liners	200.00	Nos/M	Sold auti
7	34.3 Chemical sludge from waste			Sold out to authorised reprocessor /vendors
	water treatment	750.00	Kg/m	Sold out to a d
8	36.1 Sludge from wet scrubbers			Sold out to authorised
	as nom wet scrubbers	25.00	Kg/m	reprocessor /vendors Incineration/
		15-15-15-1	10000000	CHWTSDF

(ii) Treatment: - NIL

Whenever due to any accident or gas leakage or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of Industry, Safety and Health, Police Station, Fire Brigade, Directorate of Health Services, Department of Explosives, Board and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emission and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.

10. Industry shall comply with following additional conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii.The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- This consent is issued as per the decision taken in the meeting of the Consent Committee of the Board held on 24/06/2011.
- 12. The Capital investment of the industry is Rs. 47.67 crores

(Milind Mhaiskar, IAS) Member Secretary

To, M/s Cipla Ltd. Plot No. D-27, MIDC Kurkumbh Tal- Daund, Dist- Pune. 413 802

Copy to:

1) RO, Pune /SRO, Pune 1.

-- They are directed to ensure the compliance of consent conditions.

2) CAO/Cess Branch/Master file.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	100000/-		23 Sep 2010	
2	20000/-	051429		Axis Bank
	20000/-	051429	01 Dec 2010	Axis Bank