Executive Summary

M/s Aayan Multitrade LLP (Operative of Banganga Sahakari Sakhar Karkhana Ltd.)

Gat no: 249, 195, 196, 197, 203, 204, 205, 206, 207, 208, 209,214,216,217,219,220,222,223,248, 250, 251, 252, 253, 254, 255, 198, 199, 215 of Ida village, Taluka Bhoom, and Dist. Osmanabad Maharashtra, 413 505

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

EXECUTIVE SUMMARY

EXECUTIVE SUMMARY

1.0 Introduction

The proposed activity for expansion of sugar unit and establishment of new syrup/molasses and Grain based distillery is being promoted by M/s Aayan Multitrade LLP.

M/s. Aayan Multitrade LLP (AMLLP) (M/s Banganga Sahakari Sakhar Karkhana Ltd.), Ida Taluka Bhoom, Dist. Osmanabad, is registered under the Maharashtra State co-op. Society 1960 vide Registration No. OSM/BHM/PRG/(A)S. 106/2000 dated 31.10.2000. The registered office of the company is located at Ida, Taluka Bhoom, and Dist. Osmanabad Maharashtra 413 505 India. The copy of company registration is enclosed as *Annexure-1*

The command area of the factory has excellent cane potential and the sugarcane grown in this area is rich in sucrose content. The industry proposes to expansion of sugarcane crushing capacity from 4000 TCD to 10000 TCD, establish 500 KLPD distillery unit based on sugarcane syrup/ C molasses/ "B" heavy molasses as a raw material to produce 500 KLPD Rectified Spirit/ Extra Neutral Alcohol/ Ethanol, 100 KLPD grain-based distillery along with 40 MW Co-generation power plant.

2.0 Project Location

The proposed expansion of sugar unit along with establishment of distillery and co-gen plant will be done within the existing project premises of the company i.e. Gat no: 249,195,196,197,203,204,205,206,207,208,209,214,216,217,219,220,222,223,248,250,251,252,2 53,254,255,198,199, 215 of Ida village, Taluka Bhoom, and Dist. Osmanabad Maharashtra 413 505 India

As per geographical co-ordinates of the project site, the proposed activity is covered under SOI Toposheet no- 47N/11, while the study area of the project (10 km radius) is falling under SOI toposheet no: 47N/11, & 47N/7. The project is located at elevation of 559 meters above mean sea.

3.0 Project Description

The command area of the factory has excellent cane potential and the sugarcane grown in this area is rich in sucrose content. The industry proposes to expansion of sugarcane crushing capacity from 4000 TCD to 10000 TCD, establish 500 KLPD distillery unit based on sugarcane syrup/ C molasses/ "B" heavy molasses as a raw material to produce 500 KLPD Rectified Spirit/ Extra Neutral Alcohol/ Ethanol, 100 KLPD grain-based distillery along with 40 MW Co-generation power plant.

During crushing season i.e. 180 days distillery will be operated with production rate of 500 KLPD using sugarcane syrup as main raw material; while during off season i.e. 150 days distillery will

M/s. Aayan Multitrade LLP.	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based
	Distillery along with 40 MW Co-generation Power Plant. EXECUTIVE SUMMARY

be under operation with production rate of 300 KLPD using molasses as source of raw material. Apart from this, the grain-based distillery of 100 KLPD capacity will be under operation for 330 days.

Also, in order to fulfill the power requirement industry purpose and export of the same to the grid; company proposed to installed additional Co-gen unit of 40 MW capacity (33 MW+7MW) plant. The total power generation rate will be 40 MW and the excess power will be sold to state electricity grid.

As per Environmental Impact Assessment Notification published by MoEF&CC vide S.O. 1533 dated 14th September, 2006 and its amendments till date, the proposed activity of the company requires prior Environmental Clearance as proposed activity is falling under schedule 1(d), 5(j), 5(g) of the EIA notification, the project is to be appraised by EAC as Category A project.

Salient features of proposed project are presented in **Table No. 1**.

Table 1: Salient Features of Project

Sr. No.	Component	Details
1	Name & Address	M/s Aayan Multitrade LLP (Operative of Banganga Sahakari
	of Company	Sakhar Karkhana Ltd.)
		Gat no: 249, 195, 196, 197, 203, 204, 205, 206, 207, 208,
		209,214,216,217,219,220,222,223,248,250,251,252,253,254,255
		,198,199, 215 of Ida village, Taluka Bhoom, and Dist.
		Osmanabad Maharashtra 413 505 India
2		Expansion of Sugar crushing capacity & Establishment of
	Product Type	Ethanol Manufacturing using Molasses, Cane Syrup and Grain
		and Cogen Plant
3	Project Type	New
4	Schedule of	
	project as per EIA	1(4) 5(;) 5(~)
	Notification,	1(d),5(j),5(g)
	2006	
5	Category of	'A'
	Project*	* - Applicability of General Condition - No Any
		Since the project is for manufacturing of molasses based ethanol
		with >100 KLPD capacity, the project will be appraised as 'A'
		Category project

Page 2		Page 2
--------	--	--------

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

6	Plot Area Details (After expansion)					
	Particulars	Area in Sq. m.	% of Total Plot Area			
1 Existing Built up area		33680.00				
2	Existing Area under utility	37500.00 6.35				
3	Proposed Built up area	32445.43	5.49			
4	Proposed Area under utility	22251.00	3.77			
5	Parking	116398.40	19.70			
6	Greenbelt	195007.60 33.01				
7	Area under road	74718.11 12.65				
8	Open space	78799.46	13.34			
	Total	590800.00	100			
7		Production Detail	ls			

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

SN	Name of Product & By-Product	Existing Proposed		Total			
Main Product from Sugar Unit (Existing: 4000 TCD Cane Crushing Capacity, Proposed after expansion:10000 TCD Capacity) and Proposed Co-gen plant of							
		40 MW capacit	Y				
1	Sugar	82800 TPA	-18180 TPA	64620 TPA			
2	Power	0	40 MW	40 MW			
By-P	_	_					
		_					
1	B Molasses	0 TPA	,	38,772 TPA			
2	C Molasses	32,400 TPA	-32,400 TPA	0 TPA			
3	Pressmud	25,200 TPA	37,800 TPA	63,000 TPA			
4	Baggasse	2,01,600 TPA	3,02,400 TPA	5,04,000 TPA			
	Main Produ	act from Proposed	l Distillery Unit				
	Rectified Spirit/ Extra		500 KLPD	500 KLPD			
	Neutral Alcohol/		(During	(During			
1	Ethanol		Season) and	Season) and			
1	(From	_		300 KLD			
	Syrup/Molasses Based		(During Off	(During Off			
	Production)		Season)	Season)			
Rectified Spirit/ Extra Neutral Alcohol/ 2 Ethanol (From Grain Based Production)		-	100 KLPD	100 KLPD			
	By-Produc	ct from Proposed	Distillery Unit				
1	Fusel Oil	-	2,700 KL/A	2,700 KL/A			
2	CO2 Gas	-	1,26,000 Tons/A	1,26,000 Tons/A			
3	DDGS	-	19,206 Tons/A	19,206 Tons/A			
4	Potash Granule Powder	-	24,218 Tons/A	24,218 Tons/A			
-							
		<u> </u>					
Deci	act Cost	Existing: 16	64.6176 Cr (INR)				
		Proposed: 550 Cr (INR)					
	1 2 By-P 1 2 3 4 Project	Proposed after expansion:10 1 Sugar 2 Power By-Product from Sugar Un Proposed afte 1 B Molasses 2 C Molasses 3 Pressmud 4 Baggasse Main Production Syrup/Molasses Based Production) Rectified Spirit/ Extra Neutral Alcohol/ Ethanol (From Syrup/Molasses Based Production) Rectified Spirit/ Extra Neutral Alcohol/ 2 Ethanol (From Grain Based Production) By-Production) By-Production CO2 Gas 3 DDGS Potash Granule Powder	Proposed after expansion:10000 TCD Capacit 40 MW capacit 1 Sugar 82800 TPA 2 Power 0 By-Product from Sugar Unit (Existing: 4000 Proposed after expansion:1000 1 B Molasses 0 TPA 2 C Molasses 32,400 TPA 3 Pressmud 25,200 TPA 4 Baggasse 2,01,600 TPA Main Product from Proposed Rectified Spirit/ Extra Neutral Alcohol/ Ethanol (From Syrup/Molasses Based Production) Rectified Spirit/ Extra Neutral Alcohol/ 2 Ethanol (From Grain Based Production) By-Product from Proposed 1 Fusel Oil - 2 CO2 Gas - 3 DDGS - 4 Potash Granule Powder - Budgetary Estima Project Cost (Indian Rs.)	Sugar 82800 TPA -18180 TPA 2 Power 0 40 MW 40			

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

b	EMP Cost (Indian		Capital Cost – 5907	'.8 Lakhs			
	Rs.)		Recurring Cost – 21	3.6 Lakhs			
9			Down Dogwinsment				
a	Proposed Power		Power Requirement ower requirement during se	22 97 MW			
а	requirement		wer requirement during se				
b	-						
U	Source	Source In-House Cogen Power Plant of 40 MW capacity					
10			Fuel Requirement				
a		Sr. No.	Fuel	Quantity			
			During Seaso	on			
		1	Bagasse for Boiler	373 MT/Day			
			40 TPH Boiler				
		2	Bagasse for Boiler	1664 MT/Day			
			175 TPH Boiler				
		3	Bagasse for Hot air	108 MT/Day			
			generator i.e. for				
	Baggase		Spent wash drying				
		During Off Season					
		1	Bagasse for Boiler	373 MT/Day			
			40 TPH Boiler				
		2	Bagasse for Boiler	234 MT/Day			
			30 TPH Boiler				
		3	Bagasse for Hot air	72 MT/Day			
			generator i.e. for				
			Spent wash drying				
b	High Speed	High Speed Existing: 203.8 Liter/Hour					
	Diesel		Proposed: 203.8 Li	ter/Hour			
	Diesei	Total: 407.6 Liter/Hour					
11		Diesel	Generator (D.G.) Detail	le .			
1.1		Diesei	Existing: 1 X 101				
	Capacity & No.		•	Proposed: 1 X 1010 kVA			
			Total: 2 X 1010 kVA				
12	1		Boiler Details	10 5577			
			Existing: 30 TPH &				
a	Steam Boiler		Proposed: 175				
	Total: 30 TPH, 40 TPH and 175 TPH						

Page 5

M/s. Aayan
Multitrade LLP

	Particular	Quantity (m ³ /day)			
15		Water Requirement			
		Total: 400 Nos.			
14	Man Power	Proposed: 300 Nos.			
		Existing: 100 Nos.			
	1	1			
		Total: 2 Nos X 6.5 m above roof			
c	D.G	Proposed: 6.5 m above roof			
		Existing: 6.5 m above roof			
	level)	generator: 22 m height			
a	(from ground	Proposed: 75 m Height (For 175 TPH Boiler) & Hot air			
0		TPH Boiler			
	Boiler Stack	Existing: Common Stack of 65 m Height (For 30 TPH and 40			
13		Stack Details			
		operation)			
		capacity will be under operation; however during off-season existing boiler of 40 TPH and 30 TPH capacity will be in			
		(During season existing boiler of 40 TPH capacity and 175 TP			

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

	Water requirement after proposed expansion		d on activity For Sugar ma to excess con- water requires treatment, exc manufacturing parking and re For Syrup / M During "B" consumption During 2 nd Cy During "C" consumption During 2 nd Cy During Syrup consumption During 2 nd Cy For Grain Ba Grain based p	densate availment for sugress condens gunit, CO2 pad areas. Tolasses based Molasses rate for districte: It will be based production: It will be sed Distiller production: 1 unit will be 1	including I able from gar and coate is used plant and for the distillery (300 KLD above 484.3 KL above 601.9 KL	Power generation: Due Sugar unit, there is no generation unit. After I for Gardening, Brick for dust suppression in Activity: D: 1st Cycle Water will be 2675 KLD, D (1.61 KL/KL) 1: 1st Cycle Water will be 3234.66 KLD, D (2.0 KL/KL) KLD): 1st Cycle Water will be 4046 KLD, D (1.69 KL/KL) (1.69 KL/KL) (100 KLD Capacity): Vater consumption rate D, During 2nd Cycle: It
16			Effluent	Load on CI	PU	
	Particulars			Quantity	y (m³/day)	
			Waste to be generated	Quan		Scheme for Management/Dispos al
	E.C.		mustiai w		Quanti	T
	Effluent generation rate after proposed expansion			Descripti on	ty (KLD)	For distillery Spentwash shall be treated using
		1	Sugar and Distillery	Sugar and Unit	it	anaerobic digester followed by MEE
			Division	effluent	325	followed by drying. Spentlees and other
				Spray- pond effluent	308.64	diluted effluent shall be treated in proposed distillery CPU

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

Cooling
Cooling Tower
Blowdow 372.2
DM 2065
Reject 206.5
Washing 100
Boiler 103.2
Other 10
Distillery Unit
1. Based on "C"
molasses
Spentlees 433.36
Raw
Spentwas 2258.6
h 8
Fermente
r washing 70
Cooling
Tower
blowdow 182
n
Pump
and 50
Vaccum 50
Sealing
OR
2. Based on "B"
heavy molasses
Spentlees 402.4
Spentwas 1684.6
h 6
Fermente 70
r washing
Cooling
Tower 182
blowdow 102
n
Pump 50
and 50

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

Sealing 3. Based on "Sugarcane Syrup Spentlees 682 Spentwas 2214 h Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees 111 Fermente r washing OR 0R 4. Based on grains Spent Uash Spent Uaes 111 Fermente r washing OR A. Based on grains Spent Uaes Spent Uaes 111 Fermente r washing OR OR A. Based on grains Spent Uaes Spent Uaes 111 Fermente r washing OR OR A. Based on grains Spent Uaes Spent Uaes In Domestic Vaccum Sealing Domestic Vascum Sealing Domestic Vascum Sealing Domestic waste shall be treated in aeration tank of CPU. The treated effluent is				Vaccum		
"Sugarcane Syrup Spentlees 682 Spentwas Spentwas h				Sealing		
"Sugarcane Syrup Spentlees 682 Spentwas Spentwas h						
Spentlees 682 Spentwas h 2214 Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees Fermente r washing Cooling Tower blowdow n 111 Lees Fermente r washing OR 4. Based on grains Spent Lees Fermente r washing Tower blowdow n Pump and Vaccum Sealing Tower blowdow n Pump and Vaccum Sealing Tower blowdow n Pump and Vaccum Sealing Domestic Waste CCombined sugar + Domestic waste shall be treated in aeration tank of CPU. The						
Spentwas h 2214 Fermente r washing Cooling Tower blowdow n						
Fermente r washing Cooling Tower blowdow n Pump and 70 Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees 111 Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day take) Domestic waste shall be treated in aeration tank of CPU. The target of filters in the strength of the stren						
r washing Cooling Tower blowdow n Pump and Vaccum Sealing OR 4. Based on grains Spent Wash Spent Wash 561 Spent Uces 111 Lees Fermente r washing Cooling Tower blowdow n Pump and 70 Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The				_	2214	
Twashing Cooling Tower blowdow n Pump and Vaccum Sealing OR 4. Based on grains Spent Wash 561 Spent Lees 111 Fermente r washing Cooling Tower blowdow n Pump and 70 Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The					100	
Tower blowdow n Pump and 70 Sealing OR 4. Based on grains Spent Wash 561 Spent Uses 111 Lees 111 Lees Fermente r washing 20 Cooling Tower blowdow n Pump and 70 Vaccum 70 Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The treated according to the streated according				r washing	100	
blowdow n Pump and Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees 1111 Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum 70 Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The						
blowdow n Pump and Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees 111 Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + Under the standard of CPU. The treated a of Sharth is in the standard of Sharth is in th					303 45	
Pump and 70 Vaccum Sealing OR 4. Based on grains Spent Wash 561 Spent 111 Lees 111 Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The treated of CPU. The				blowdow	303.13	
and Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees 111 Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (CCombined sugar + 48 m³/day Tower towaste waste shall be treated in aeration tank of CPU. The						
Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees 111 Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The						
Vaccum Sealing OR 4. Based on grains Spent Wash Spent Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The					70	
OR 4. Based on grains Spent Wash Spent Lees 111 Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m²/day Domestic waste shall be treated in aeration tank of CPU. The					, 0	
4. Based on grains Spent Wash Spent Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day A. Based on grains Spent Wash 561 Spent Lees Fermente r washing 20 Cooling Tower blowdow n Pump and Vaccum Sealing Domestic waste shall be treated in aeration tank of CPU. The						
Spent Wash 561 Spent 111 Lees 111 Fermente 20 r washing Tower 84 blowdow n Pump and 70 Vaccum Sealing Domestic waste shall be treated in aeration tank of CPU. The treated of fluents in the streat of the sugar + to the sugar of fluents in the streat of the sugar in the streat of the sugar in the s						
Wash Spent Lees 111 Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The					n grains	
Lees Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The					561	
Fermente r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Tower blowdow A But the control of the co					111	
r washing Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Tower blowdow n Pump and Vaccum Sealing Domestic waste shall be treated in aeration tank of CPU. The					111	
Cooling Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Tower 84 Domestic waste shall be treated in aeration tank of CPU. The					20	
Tower blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day 48 m³/day Tower blowdow N Domestic waste shall be treated in aeration tank of CPU. The						
blowdow n Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day blowdow n Pump and 70 Vaccum Sealing Domestic waste shall be treated in aeration tank of CPU. The						
Domestic Waste (Combined sugar + 48 m³/day 48 m³/day treated a officient is					84	
Pump and Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day Domestic waste shall be treated in aeration tank of CPU. The						
Domestic Waste (Combined sugar + 48 m³/day and Vaccum Sealing Domestic waste shall be treated in aeration tank of CPU. The						
Vaccum Sealing Domestic Waste (Combined sugar + 48 m³/day To Domestic waste shall be treated in aeration tank of CPU. The						
Domestic Waste Combined sugar + Sealing Domestic waste shall be treated in aeration tank of CPU. The					70	
Domestic Waste Waste (Combined sugar + 48 m³/day tracted afficient is						
Waste (Combined sugar + 48 m³/day be treated in aeration tank of CPU. The			Domostic	Sealing		D
2 (Combined sugar + 48 m³/day tank of CPU. The						
sugar + treated officert is		2	(Combined	48 m³/day		
destallows						
distillery division) being used for			distillery			

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

EXECUTIVE SUMMARY

					gardening /greenbelt
					development
17			CP	U Capacity	
a	Capacity of		ETP for	Sugar and Co	gen Unit: 7000 KLD
	ETP/CPU		CPU for Distillery Unit: 3500 KLD		
18]	Details of l	Hazardous Wa	nstes
Sr.	Particulars	Categ	UOM	Quantity	Method of
No.	raruculais	ory*	UOM	Quantity	Disposal/Management
a	Used/Spent Oil	5.1	KL/A	1.01	Disposal through MPCB
а	Osed/Spent On	3.1	KL/A	1.01	authorised recycler
*Schedule I of The Hazardous and Other Wastes (Management and Trans boundary					gement and Trans boundary
		M	Iovement)	Rules, 2016.	
19	Details of Non-Hazardous Solid Wastes				
Sr.	Particulars	Categ	UOM	Quantity	Method of
No.	raruculais	ory	UOM	Quantity	Disposal/Management
	Poilor Ash		TPA	7330.32	Sell to brick manufacturing
a	Boiler Ash	-	IPA	/330.32	unit
h	CPU Sludge		TPD	6.4	It will be used/ sell as manure
b		_		(Max)	it will be used/sell as manure

4.0 Description of the Environment

Primary baseline environmental monitoring studies in 10-km radius study area were conducted through NABL approved laboratory – **Shreeji Aqua Laboratories** during March 2022 - May 2022.

4.1 Topography, Land use & its Classification

Thematic manuscript for contour layer was generated from Survey of India toposheet at 1:50,000 scale. After scanning coverage was generated. Coverage was edited to remove all errors of dangle. Attribute value was given to each contour in the coverage. The site not having much undulation. The site is having general slope from south to north i.e. towards the river.

4.2 Soil Environment

The soil samples were derived from 8 different locations within the study area of the project. Analysis results of the same, revealed that the pH values of soil samples were varying in range of 7.20 to 7.50; which indicated Neutral to slightly alkaline nature of soil samples. The organic matter

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

EXECUTIVE SUMMARY

content in soils was varying between the range from 2.02-3.21 percent. The values for Nitrogen at all locations varied between 224.6 to 291.3 mg/Kg. & maximum concentration of Nitrogen was observed at location S4. Concentration of Phosphate were found to be in the range of 48.6 to 64.5 mg/kg. whereas highest concentration was observed at location S6, while the lowest concentration was observed at location S5. Concentration of potassium amongst all locations was found to be ranging between 49.6 to 65.3 kg/ha. Heavy metals viz.As, Cr, Hg & Pb were below detection limit.

4.3 Air Environment

Ambient Air quality for criteria pollutants viz. PM10, PM2.5, NOx, SO₂ and CO was monitored at eight (8) locations in study area whereas additional parameters viz. NH₃, C6H6, BaP, O₃, Pb and Ni, along with criteria pollutants were monitored at proposed project location.

Particulate Matter (PM₁₀)

The study reveals that maximum concentration was observed to be in the range of 50.2-77.1 $\mu g/m^3$. The highest 24-hourly concentration was recorded at sampling location A1. At the same time minimum concentration was observed at location A7. The average concentration of PM $_{10}$ can be said to be ranged between 44.8-71.41 $\mu g/m^3$. The high average concentration of particulate matter recorded at project site (A1) due to operation of sugar unit, vehicular movement on internal and nearby roads. During baseline period the sugar unit was operational. It should be noted that the concentration of PM $_{10}$ was not observed to be exceeding the standards prescribed by the CPCB on any occasion.

Particulate Matter (PM 2.5)

The major source of $PM_{2.5}$ is said to be the combustion of fuels, fire wood and industrial emissions etc, present within study area. The maximum of $PM_{2.5}$ (43.6 $\mu g/m^3$) during the study period was recorded at location A1, whereas the minimum value (12.6 $\mu g/m^3$) concentration was recorded at A1 & A5 location . The average concentration of $PM_{2.5}$ during the study period was computed to be in the range of 18.5-37.28 $\mu g/m^3$.

Sulphur Dioxide (SOx)

High level of SO_X in ambient air indicates the presence of combustion of fossil fuel in the vicinity. The ambient air monitoring results indicate that the highest concentration of SO_X is experienced at A1. The burning of fuel in existing boiler is main source of emission for SO_X . The average concentration of SO_X recorded during the study period ranged between 13.83-25.20 $\mu g/m^3$ rospectively. It should be noted that maximum average concentration was recorded at location A1 while the lowest can be observed at location A7.

Oxides of Nitrogen (NOx)

|--|

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

EXECUTIVE SUMMARY

The various forms of Nitrogen in NO, NO₂ and N₂O are collectively called as Oxides of Nitrogen. The highest value of NO_X during the monitoring period was observed at location A1 while the minimum average was recorded at A7. The average concentrations were in the range of 17.97-32.67 μ g/m³. The maximum 24 hourly value of NO_X was recorded at the monitoring location A1 (35.4 μ g/m³) whereas the minimum concentration of NO_X was recorded at location A7 (13.8 μ g/m³).

Carbon Monoxide (CO)

The anthropogenic source of CO is due to incomplete combustion of fuel majorly in absence of air. The maximum concentration of CO estimated at all locations during the study period can be observed is 0.07-1.1 mg/m³.

All the parameters were found to be within the desired limits specified by NAAQ Standard.

Additional Parameters

From the monitoring results of additional parameters as given in **Table 3.20**, it is evident that Ozone, Lead, Ammonia, Benzene, Benzo (a) pyrene, Arsenic, Nickel and VOC's were below detection limit.

Thus it is concluded that the concentration of additional parameters at project was also within the prescribed NAAQS, 2009.

4.4 Noise Environment

Ambient noise levels were monitored at eight (8) locations in the study area during the study period.

Industrial Zone

The day time noise level at the project premises was observed to be 61.95 dB (A) while during night time the noise level was recorded to be 52.08 dB (A). It shall be noted that the noise levels during the day time as well as night time were estimated to be under the prescribed standards by CPCB.

Residential Zone

The minimum noise level recorded during the daytime was observed at location N5, whereas the maximum noise levels can be observed at location N3. The location N3 is well populated in the surroundings. It shall be noted that the permissible limits for noise did not exceed at any of the locations selected for sampling.

4.5 Ground Water Environment

The results revealed that values/ concentrations of various parameters amongst all the samples were in the range of pH - 7.20 to 7.60, TDS - 401.2 to 477.3 mg/l, Sulphates - 58.7 to 79.6 mg/l,

Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.

EXECUTIVE SUMMARY

Phosphates – 1.72 to 2.28 mg/l, Total Hardness – 160.2 to 194.2 mg/l, Nitrate – 15.2 to 23.6 mg/l, Bicarbonate – 20.2 to 34.4 mg/l, Calcium – 40.8 to 48.6 mg/l, Sodium – 47.5 to 65.3 mg/l, Potassium 24.6 to 39.6 mg/l, Magnesium – 14.3 to 18.2 mg/l, COD - <5.0 mg/l, BOD - <1.0 mg/l, whereas concentrations of Arsenic, Lead were <0.01 mg/l and that of Cadmium, Iron, Chromium, Mercury, Nickel & Zinc were below detection limit. Total Coliforms & E. Coli were <2 No/100ml in all samples.

4.6 Surface Water Environment

The quality assurance for collected data has been done. The values were checked and found to be in co-relation as per Ionic balancing done for the each sample report.

Surface water samples were derived from 4 locations in different surface water bodies within study area, analysis results of the same revealed that pH values amongst all samples varied in the range of 7.20 to 7.50, Total Hardness concentration varied in the range of 126.1 mg/l to 159.8 mg/l & maximum concentration was recorded at SW1, TDS concentration varied in the range of 319.6 to 408.9 mg/l whereas maximum concentration 408.9 mg/l was recorded at SW1 & minimum concentration 319.6 mg/l at SW3. Electrical Conductivity was found to be ranging in between 490.2 to 621.3 μ S/cm. The concentrations of Dissolved Oxygen, BOD & COD were found to be varying in the range of 3.4 to 3.8 mg/l, 3.0 to 5.0 mg/l & 9 to 15 mg/l respectively whereas the concentrations of Phosphates, Nitrate & Ammonical Nitrogen varied in the range of 3.31 to 4.02 mg/l, 13.6 to 21.2 mg/l & <0.01 mg/l respectively.

Concentrations of elements such as Calcium, Sodium & Potassium were found to be in the range of 33.9 to 41.6 mg/l, 40.1 to 53.6 mg/l & 9.68 to 17.6 mg/l respectively.

Heavy metals viz. Lead, Chromium, Mercury, Cadmium, Arsenic & Nickel were below detection limits in all samples

To ascertain the best suited use of sampled surface water bodies, the analysis results were compared with the Designated Best Use Water Quality Criteria & the analysis revealed that sampled surface water bodies in study area be suited for Class "E" Water i.e., Irrigation, Industrial Cooling, Controlled waste disposal.

4.7 Biotic Environment

Project site and surrounding area of site comes under dry deciduous and southern thorn forest types (Chmapion and Seth 1968). Mixed forest consisting of various varieties of species the occurrence of which is considerably influenced by biotic interferences and management. Major tree species occurring in the forest can be listed as Teak, Anjan, Arjun, Bel, Babul, Khair, Palas, Parijatak etc.

Distinctly along with 40 MW Co-generation Power Plant.	M/s. Aayan Multitrade LLP.	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.
--	-------------------------------	---

Growth of plants quite stunted because of poor soil quality but growth of grasses is abundant in all areas. Major land is covered with scrub forest which is uneconomic and thorny species.

Biological environment of the area was studied during the study period. No endangered species have been sighted in the area. No Wildlife Sanctuary, National Park, Biosphere Reserves, Wildlife Corridors exists within study area of 10 km radius.

4.8 Socio-Economic Environment

The 10 km study area includes seven Taluka of Osmanabad District. There are total 41 villages in the study area. The study area is essentially urban in nature. The socio economics of study area is studied through primary and secondary survey. The socio-economic aspects of the study area are summarized in the table given below.

Table 2: Summary of Socio-Economic Aspects

Demographic Parameters	Details
No. of States	1
No. of District	1
No. of Tehsil	2
No. of Villages	41
Total No. of Households	12,773
Total Population	57,990
Child Population	6,727
Scheduled Castes	6,571
Scheduled Tribes	715
Litamagy (Ayamaga)	Average:
Literacy (Average)	74.38%
Total Workers	32,383
Main Workers	29,044
Marginal Workers	3,339

Source: Primary Census Abstract & DCHB 2011, Osmanabad District, State Maharashtra

M/s. Aayan Multitrade LLP.	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.
	EXECUTIVE SUMMARY

5.0 Anticipated Environmental Impacts and Mitigation Measures

Table 3: Summary of Impacts & Mitigations

Sr. No	Environmental Parameters	Aspect Attributes	Anticipated Impacts	Proposed Mitigation Measures
		Construc	ction Phase	
1.	Air Quality	Dust during handling of cement/concrete/stone aggregates & other construction materials.	The estimated generation would be around 9.62 tons/month of the activity. Exposure of construction workers to such dusts may lead to short term respiratory problems, whereas, prolonged & continuous exposure may lead to malfunctioning of lungs. The anticipated construction period will be 8 months after grant of all Environmental Clearance, Consent To Establish & all other Statutory Permissions.	Proper loading and unloading of the materials to ensure minimum dust. Managing & covering the stockpiles. Regular sprinkling of water on the working site, Installing wind barriers around working site & all around the plot boundary for containing the dust.
2.	Noise Levels	Noise generated from construction machineries like Poclain, Lift Crane, Jack Hammer Drill, Digger, Compactor, Roller etc. & by use of construction equipments like Jack Hammer, Cutter, Drill Concrete	It is anticipated that the cumulative noise levels by all construction machineries, equipments & activities at propagating at plant boundary will be in the range of 13.81 dBA to 16.75 dBA & propagating intensity of noise at	PPEs viz. Ear Plugs/Muffs will be provided to workers, Construction activities will be limited from 9.00 AM to 5.00 PM, Installation of noise barriers around project plot will further minimize the intensity of propagating noise.

Page 15
1 age 13

M/s. Aayan
•
Multitrade LLP.

3.	Water Quality	vibrator etc. and by arrival & depart of transport vehicles. Surface runoff generated Water used for construction activities mainly for concrete mixing, sprinkling etc. Sanitation waste water by construction workers.	distance of 100 m from plot will be 13.24 dBA, thus significant impacts outside plant premises are not anticipated. If such runoff water & sanitation waste water finds way to surrounding soils & water body, may lead to contamination of surrounding soils & increased turbidity & contamination in water body.	The surface runoff generated during construction activities will be properly filtered and utilised for gardening or sprinkling & Mobile sanitation facilities will be provided to workers which will be periodically cleaned through night soil tankers.
4.	Construction & Demolition Wastes Management	Proposed project being a green field project demolition waste will not occur however inert construction wastes such as: Cardboards, Wooden Boxes, Wooden planks, Metal rods, HDPE bags, Felled Concrete, Stones, Aggregates & debris will are anticipated to be generated. Excavated/Dug soil/earth will be generated during site preparation activities.	Haphazard handling of such wastes may lead to advent of Rodents, Reptiles within project plot, thereby causing dangers to workers working on site. Disposal of such wastes on land will lead to degradation of soils.	Excavated/ dug soil/earth will be stored appropriately in dedicated space within project plot & will be used for green belt development activity along with mix of new soil. Inert construction wastes viz. Cardboards, Wooden Boxes, Wooden planks, Metal rods, HDPE bags will be stored in dedicated space & sold to recyclers.

M/s. Aayan	
Multitrade LLP.	

				Felled Concrete, Stones,
				Aggregates & debris will be used
				as filling material for internal
				roads in consonance with
				Construction & Demolition
				Wastes Management Rules 2016.
		Operation	onal Phase	
1.	Air Quality	Utilities stack emissions viz.	The anticipated maximum	1. In current practice, Scrubber is
		Particulate Matter, SO ₂ , NOx &	concentration of PM ₁₀ from steam	attached to combined stack of 65
		CO from boiler & D.G operations	boiler operations will be 0.54	metet height for existing boiler of
		& Process emissions viz. CO ₂ &	μ g/m ³ , maximum concentration of	30 TPH and 40 TPH Capacity
		VOC's.	SO ₂ will be 5.24 & that of NOx	2. After expansion; for additional
			will be 3.04 g/m ³ which are likely	boiler of 175 TPH capacity, ESP
		VOC emission generated due to	to be carried in downwind	followed by Scrubber system and
		the handling and storage of the	direction.	Stack of 75 meters height will be
		Ethanol.		provided.
			Anticipated health effects: People	3. For Sepnt wash dryer (Hot air
			in downwind localities if prone to	generator based) Scrubber
			continuous & prolonged emissions	followed by Stack of 22 meter
		Fugitive emissions from material	may be susceptible to adverse	height will be provided
		transport vehicles.	health impacts related to	
		_	respiratory & pulmonary due to	4. D.G will be provided with a
			particulate matter. Carbon	stack of 6.5 m above roof as per
			monoxide decreases the oxygen	CPCB guidelines for proper
			carrying capacity of the blood by	dispersion of emissions.
			reducing the haemoglobin.	_

M/s. Aayan Multitrade LLP.	Draft Environmental Impact Assessm (Operative of M/s Banganga Sahakari existing 4000 TCD Sugar Unit upto 10 Sugarcane Syrup/"C"/"B" Heavy Mo Distillery along with 40 MW Co-gener	Sakhar Karkhana Ltd.) for Proposed 1000 TCD capacity and Establishment blasses based Distillery, 100 KLPD	Expansion of of 500 KLPD
		EXECUTIVE S	UMMARY
		The anticipated process nerations are CO2- 453 TPD, Which will be sent to CO2 recovery plant.	5. CO2 Bottling plant is proposed for recovery of process emission.6. Provision of closed feeding system for solvents.
		The health effects related to OC's are eye, nose and throat irritation headaches. Environmental effects:	7. The roads within the premises will be paved to avoid the dust generation from vehicular activity.
	tin su l bio	air emissions in long course of me may affect the immediate arrounding vegetation stature ohysically (leaf senescence, hampered growth etc.) & ologically thus may affect the verall surrounding ecology.	 68. It will be ensured that all the transportation vehicles have a valid PUC (Pollution under Control) Certificate. 9. Regular sweeping of all the roads & floors will be done to avoid fugitive dust.
			10. The proposed thick green bel of 10 m width along the plant periphery will help to capture the fugitive emissions.

Page 18

	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP.
	(Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of
M/s. Aayan	existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD
Multitrade LLP.	Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based
Multitude LLI.	Distillery along with 40 MW Co-generation Power Plant.
	EXECUTIVE SUMMARY

				concentrations exceed the prescribed CPCB/Consented
				standards.
2.	Noise Quality	Operation of Steam Boilers,	It is anticipated that the cumulative	1. Acoustic enclosures will be
		Cooling Towers, Pumps, Blowers	noise levels by all machineries,	provided to high noise generating
		& material transport vehicles.	equipments & operation activities	equipments for attenuation of
			at propagating at plant boundary	noise level during operation.
			will be in the range of 0 dBA to 0	
			0.10 dBA.	2. Steam boilers will be placed in
				a confined space viz. boiler house
			Impacts of exposure to continuous	where the surrounding walls will
			& prolonged noise would be	acts as a barrier for propagating
			Temporary/Permanent hearing	noise.
			loss,	3. PPE's viz. Ear muffs/plugs will
			Mental disturbances	be provided to workers working
			Increase in heart rate	near noise generating equipments.
			Reduced workers performance due	
			to psychiatric disorder	4. The proposed thick green belt
			and Tinnitus in case of high level	of 10-20 m width along the plant
			of noise exposure on regular basis.	periphery will help to further
				minimise the intensity of
			The intensity of propagating noise	propagating noise out of plant
			at a distance of 100 m from plot	premises.
			boundary will be almost nil, thus	
			significant impacts outside plant	
			premises are not anticipated.	

M/s. Aayan
Multitrade LLP.

3.	Water Quality	1. Effluent from process,	The anticipated treated effluent	
		washings, Backwashes.	characteristics area: pH - 7.5 to	For efficient treatemnet of the
		2. Boiler & Cooling Tower blow-	8.0, TSS < 100 mg/lit., BOD < 100	spent wash separated using
		downs.	mg/lit., COD < 250 mg/lit., TDS <	analyser coloumn, MEE followed
		3. Domestic wastewater.	2100 mg/lit. and Oil & Grease <	by Spent wash dryer will be
			10 mg/lit.	installed; The condensate from
				MEE unit will be collected and it
			Accidental/Deliberate release of	will be further treated in CPU
			treated/un-treated effluents in	along with other effluent streams
			surface water bodies may lead to	like Spent Lees, Blowdowns from
			contamination/ eutrophication/	Boiler and Cooling Towers,
			acidification/ toxification of the	Sealing water, WTP reject and
			subjected water bodies and in of	Washing effluent.
			case land may lead to complete	
			degradation of subjected land	The CPU will be consist of
			affecting, also may contaminate	Primary, Secondary and Tertiary
			the ground water by way of	unit
			percolation.	
				Domestic effluent load will be
			Such affected soils, Surface water	connected and treated in
			& ground water sources cannot be	secondary treatment facility.
			used for any purpose & depending	
			terrestrial & aquatic ecology will	
			be completely affected.	
4.	Solid Waste	1. Hazardous waste i.e. Spent oil	Unscientific handling & disposal	1. Spent oil generated from
	Management -	generated from DG and	may lead to contamination of	project activities will be handled,
	Hazardous	maintainance of the plant.	surrounding soils, water sources &	stored and diposed as per

M/s. Aayan
Multitrade LLP.

		2. Hazardous waste generated from maintenance operations.	there by affecting the ecology & health of the workers coming in direct contact with the hazardous waste like skin allergies/rashes/burns etc.	Hazardous Waste Management Rule, 2016 and its amendments till date. Mainly it will be sold to MPCB authorised vendor.
5	Solid Waste Management (Non Hazardous Inert Waste)	1. Scrap Metal 2. Scrap Plastic 3. Office Waste 4.Canteen Waste 5. Wooden Pallets 6. Boiler Ash 7. CPU Sludge 8. Yeast Sludge	Hap-hazard handling & storage may lead to inadequate open space in plant premises & it may lead to rodent breeding thereby affecting the occupational health & environment.	 Designated area for Scrap materials (Metal, Plastic, Wooden Pallets, Office Waste) storage will be provided in the plant. Scrap materials will be recycled through scrap vendors. Daily housekeeping waste and canteen waste will be disposed through vermin composting facility (off-site). Boiler ash – 7330.32 TPA will be used in brick manufacturing unit CPU Sludge- 6.4 TPD (MAX), will be used/sold as Manuare

M/s. Aayan Multitrade LLP.	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP. (Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based Distillery along with 40 MW Co-generation Power Plant.
	EXECUTIVE SUMMARY

	EXECUTIVE SUMMARY
Widitidade EEF.	Distillery along with 40 MW Co-generation Power Plant.
Multitrade LLP.	Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based
M/s. Aayan	existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD
	(Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of
	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP.

6.0 Quantitative Risk Assessment and Mitigation Measures

Quantitative Risk for proposed project have been assessed based on ALOHA for tank storages.

Based on the unsafe distances plotted in ALOHA software output, the MCLS (Maximum Credible Loss Scenario) for proposed factory is identified for Ethanol & the anticipated effect distance is 157 from Ethanol PESO area in factory premises.

The scenario considered for assessing the impact by quantitative risk assessment was taken from Thermal radiation from pool fire

7.0 Disaster Management Plan

Disaster Management Plan will be implemented in consultation with the District Administration to take care of health and safety during any untoward incident.

In view of handling of processes in industry, On-site Emergency Plans are important and hence has been prepared for the industry. Additionally recommendations for and Off-site shall be provided to the District Administration. During operational phase, surrounding population shall be made aware of safety precautions to be taken in case of any emergency situation due to the overall project activity.

8.0 Occupational Safety & Health Management

The Project Proponent shall continue to strictly adhere to the rules of Factories Act 1948 & the Maharashtra Factories Rules, 1963 regarding the occupational health facilities to be provided to the workers of the company.

- Industry will provided decontamination facilities for the workers. The health records of the workers will be maintained.
- For the continuous and continual development, company will continue to train & educate the operators and workers with the environment, health & safety rules & regulation, procedure and measures.
- Periodic medical check-ups will be carried out to ensure the health status of the all workers.
- Job rotation will be done.

9.0 Post Project Environmental Monitoring Plan

Post project environmental status will be evaluated as per the Environmental Monitoring Plan framed in EIA along with additional parameters suggested if any Statutory Clearances/Permissions and frequency of environmental attributes including monitoring locations will be as per the guidelines provided by MoEF&CC/CPCB/MPCB. Monitoring shall be carried out by third party laboratories that are accredited by NABL and/or MoEF&CC.

Page 23	

	EXECUTIVE SUMMARY
Widitiade EET.	Distillery along with 40 MW Co-generation Power Plant.
M/s. Aayan Multitrade LLP.	Sugarcane Syrup/"C"/"B" Heavy Molasses based Distillery, 100 KLPD Grain Based
	existing 4000 TCD Sugar Unit upto 10000 TCD capacity and Establishment of 500 KLPD
	(Operative of M/s Banganga Sahakari Sakhar Karkhana Ltd.) for Proposed Expansion of
	Draft Environmental Impact Assessment (EIA) Report of M/s Aayan Multitrade LLP.

10.0 Environmental Management Plan

Conduction of Environmental monitoring program as per plan, periodic reviews & audits will be carried out for effective environmental management. Project Management along with EHS department will ensure overall effective implementation of the management plan.

Systems will be in place to ensure compliance of all environmental statutory requirements & obligations and it will be ensured.

All recommendations given in the EIA report including that of occupational health, risk mitigation and safety shall be complied. Company have allocated Indian Rs 59.078 Cr for environmental pollution control measures & environment management plan activities; which is ~10.7 % of total project cost.

11.0 Project Benefits

The following benefits are expected from the proposed project:

- This project will have locale specific positive social and economic benefits.
- Some of these would be direct benefits of long term nature.
- The project will generate revenue for the State Government.
- The project will create additional direct/indirect employment at various downstream & upstream ends and largely for local people.
- Local people will be preferred for employment during the construction and operation stage.

12.0 Corporate Environment Responsibility (CER) Action Plan

Ideally CER planning is envisioned from the perspective of need based assistance in health, education, sustainable lifestyles, social mobilization, infrastructure, water harvesting, agriculture and environmental protection taking into consideration locale specific scenarios around the project area.

Company will carry out its duties under Corporate Environment Responsibility (CER) as per the MoEF&CC Office Memorandum - F.No.22-65/2017-IA.III dtd. 30th September 2020, by virtue of which the CER activities will be implemented as part of Environment Management Plan.

CER cost of 0.5% of proposed project cost viz. 2.75 Cr is allocated for implementation of need based CER activities in project area.